



NAPIER
CITY COUNCIL
Te Kaunihera o Ahuriri

Napier Civic Building
231 Hastings Street
t +64 6 835 7579
e info@napier.govt.nz
www.napier.govt.nz

STRATEGY AND INFRASTRUCTURE COMMITTEE

Open Attachments Under Separate Cover

Meeting Date: Tuesday 19 March 2019

Time: 3pm

Venue: Council Chambers
Hawke's Bay Regional Council
159 Dalton Street
Napier

TABLE OF CONTENTS

Item 1	Napier Aquatic Centre Development: Completing LTP Caveats	
Attachment A	Onekawa Park Development Plan	2
Attachment B	Napier Aquatic Centre Concept Design	9
Attachment C	Enlarged birthday party room	31
Attachment D	Tonkin & Taylor Geotechnical Report: Prebensen Drive Proposed Aquatic Site	33
Attachment E	Ashburton EA Networks Centre: Case Study.....	199



Onekawa Park Development Plan

Overview

Vision

- NCC have an opportunity with the relocation of the Aquatic Centre to transform Onekawa Park into a recreational space loved by residents and supporting our community to be more active.


Overview

Suburb:	Onekawa
Location:	48, 50 Flanders Avenue
Total area of reserve:	8.5766 ha

This area was set aside in 1946 when the first part of Onekawa was planned for residential sites. Parts of the park were used for a dump whilst the remainder was leased for grazing purposes. The legacy from the dumping areas is all too evident in the form of broken glass, bricks and stones and other rubbish in the surface soil. Onekawa Park was chosen as the site for the Olympic Pool and this swimming complex was completed and opened in December 1964. Later, 12 all weather tennis courts were constructed next to the pool and these were opened for play in December 1966.

The courts were extensively renovated in 1990. The courts are also used in winter for netball. In 1974 the indoor heated pool was opened. Exhibition courts for netball and tennis were constructed in 1983.

The predominant uses are swimming all year round, tennis in summer and netball in winter. The park is also used as a neighbourhood reserve and children's play area. A kindergarten occupies part of the reserve.



High Level Consultation Plan

An Onekawa Park Development Working Group will be established at the outset of the project, which will coordinate consultation on the Park's development as part of its role. The composition of this group should include representation from council, council officers and members from within the community.

Several layers of consultation will be implemented to ensure there are appropriate and relevant opportunities for the community and key stakeholders to contribute to development of Onekawa Park following relocation of the Napier Aquatic Centre.


Key stakeholders to be engaged with during the masterplan development process include:

- Plunket
- Omni-gym
- Hawkes Bay Netball
- Onekawa Kindergarten
- Age Concern
- Cancer Society
- Disability Advisory Group
- Zeal
- Sport Hawke's Bay
- Local childcare centres
- Local schools (including Onekawa School, Saint Patrick's School, William Colenso College)
- Local businesses
- Local and neighbouring residents

It is anticipated there will be three stages of consultation – pre-engagement (informal), engagement (informal), and consultation (formal).

A detailed consultation plan will be required, which will identify the key stakeholder groups, specific timings and the tools to be used at each stage.

Consultation stage	Focus	Audience	Timing
Stage 1: Pre-engagement	Awareness raising Idea, theme generation	Working Group Key stakeholders Community	4-6 weeks
Stage 2: Engagement on concept/s	Awareness raising Feedback	Key stakeholders Community	4-6 weeks



Stage 3: Formal consultation on design/s	Encourage formal submissions	Affected parties Key stakeholders Community	6 weeks
Communications on final design	Inform via media	All	Following design approval

Note: Timings are not necessarily consecutive and will align with the overall project management plan phases.




Project Funding

Included in the LTP budget is:

- \$500,000 in the 2019/20 financial year for demolition of existing facility and returning the site to reserve. Project timeline delays will mean that this amount will need to be carried over to the following financial year when the completion of the new facility is now scheduled.
- \$700,000 in 2023/24 financial year for implementation of the Master Plan for the reserve. It is intended to bring this forward to year one of the 2021/22 - 2031/32 Long Term Plan.
- Dependant on the master planning process, council vision for Onekawa and the community consultation, council will have the opportunity to review and allocate funding required.

Project Plan

ONEKAWA PARK DEVELOPMENT PLAN: Project Plan



What will stay?

- ### Optional Enhancement

- ### Other Opportunities

- A. Children's / young adult play equipment
 - * Playground
 - * Skatebowl
 - * Climbing structures
- B. Improved Amenity / Greenspace
- C. Passive & Active Recreation
 - * Informal - walking, resting, biking, Tai chi, dog walking, scootering
 - * Formal - Ki-O-Rahi, basketball, touch rugby, CrossFit.



WM WARREN AND MAHONEY®

NAPIER AQUATIC CENTRE

CONCEPT DESIGN

—
Revision 2.0

—
February 2019



DESIGN PRINCIPLES

WELLNESS

OPERATIONAL EFFICIENCY

→ A simple building arrangement allows separation of wet and dry components.

INTUITIVE & LEGIBLE

- Hydrosides provide visual landmark for the facility from the main road.
- Controlled glazing to the pool hall provides views to the park to the North West whilst controlling glare.
- Fitness areas and studios are placed on display, activating outdoor space and providing visual beacon from State Highway 2
- Visual connections provide passive surveillance of the shared green space and the car park and are a significant component of CPTED design for the facility

ACCESS

- Public access provided from Tamatea Drive
- Service access is to the South East of building

SOCIAL SPACE

- A shared green / sporting space for the community to use
- Park like nature, with grassed areas, picnic spaces, swing ball

SHELTER

- External spaces are orientated to be protected from the prevailing nor-easterly wind
- Afternoon sunshine is captured in west facing areas providing amenity for the cafe outdoor seating area and the shared green space

FUTURE FLEXIBILITY

- Provision has been made to enable the construction of an additional pool to the east end of the pool hall in future.

SITE ANALYSIS

LOCATION PLAN


Not To Scale



DESIGN RESPONSE

SITE PLAN

Not To Scale



DESIGN RESPONSE


DESIGN CHANGES FROM QEII

1:500 @ A3

The following design changes and developments have been incorporated to respond to operator feedback and the Napier Aquatic Brief.

LEGEND:

- A** SECOND BODY SLIDE ADDED TO PROVIDE A TOTAL OF TWO WATER SLIDES
- B** FUTURE OUTDOOR AREA
- C** DEEPER BODY OF WATER INCLUDED FOR BOMBING / AQUA CLIMBING IN MAIN POOL
- D** WARM WATER POOL SPACES (WWP / SPA / SAUNA / STEAM) LOCATED CLOSER TO CHANGE ROOMS TO ALLOW SPACE FOR FUTURE POOL EXPANSION
- E** CHANGING ROOMS ENLARGED AND WET / DRY SEPERATION ACHIEVED FOR BETTER OPERATIONAL OUTCOMES
- F** CAFE WET LOUNGE CREATED ACCESSED FROM POOLSIDE
- G** FOYER AND RECEPTION ADJUSTED TO RESPOND TO ENTRY FROM SOUTH.
- H** RETAIL AREA CREATED ADJACENT TO THE FOYER SPACE FOR IMPROVED FLOW
- J** DRY CHANGE ROOMS RE-PLANNED TO IMPROVE LAYOUT
- K** SPECTATOR SEATING AREA INCREASED TO PROVIDE SEATING CAPACITY FOR APPROXIMATELY 250
- L** ADDITIONAL TWO LANES ADDED TO LEARN TO SWIM POOL



DESIGN RESPONSE

OUTDOOR AREA: DRY SIDE ENTRY

The building entry faces the Tamatea Drive to the West and is immediately visible on approach creating a clear and legible entry sequence. This provides an opportunity to create an active civic address to the building which can be developed to provide a range of informal recreation opportunities.

The cafe location is designed to service the wet pool side and the dry side and will activate the main entrance by servicing a dry seating area adjacent to the foyer and an outdoor undercover seating area.

It is envisaged that the outdoor civic entry would be activated by integrating play, recreation and informal seating spaces into the landscape.

MAIN ENTRANCE



URBAN PLAY AREA



DRY SIDE CAFE



NATIVE PLANTING AND FENCING



SEATING PLATFORMS




EXTERIOR MATERIALS



WHITE KINGSPAN PANEL



TRANSLUCENT POLYCARBONATE




PRECAST CONCRETE

INTERIOR PRECEDENTS



POOL HALL




CHANGE BLOCK


MASSING











+

Proposed Napier Aquatic Centre


Prebensen Drive, Napier

Prepared for
Napier City Council

Prepared by
Tonkin & Taylor Ltd

Date
June 2018

Job Number
1006598.v1



Exceptional thinking together
www.tonkintaylor.co.nz

Distribution:

Napier City Council

Electronic copy

Halcyon Project Management

Electronic copy

Tonkin & Taylor Ltd (FILE)

1 copy

Table of contents

1	Introduction	1
1.1	General / Scope	1
1.2	Site Description	2
1.3	Proposed development	3
2	Desktop Review	3
2.1	Historical Aerial Photography	3
2.2	Published geology	4
2.3	Historical Geotechnical Investigations	4
3	Geotechnical Investigations (T+T 2018)	4
3.1	Site Investigations	4
3.2	Laboratory Testing	5
4	Subsurface Conditions	5
4.1	Site Stratigraphy	5
4.2	Groundwater	6
5	Geotechnical Considerations	7
5.1	General	7
5.2	Seismic shaking hazard	7
5.2.1	Seismic site subsoil class	7
5.2.2	Ground shaking hazard	7
5.3	Liquefaction assessment	8
5.3.1	Liquefaction susceptibility	8
5.3.2	Liquefaction potential	8
5.3.3	Consequences of Liquefaction	9
5.3.4	Lateral Spreading	9
5.3.5	Discussion	10
5.4	Consolidation Settlement	13
5.4.1	Settlement monitoring	14
5.5	Foundation Considerations	14
5.5.1	Zone 1 Foundations	14
5.5.2	Zone 2 Ground Improvement and Foundations	14
5.5.3	Zone 3 Foundations	15
5.5.4	Services	15
5.6	Earthworks Considerations	15
5.6.1	General	15
5.6.2	Structural Fill	16
6	Pavement Design	16
7	Retention Design and Groundwater Control	17
8	Conclusions and Recommendations	18
9	Applicability	19

- Appendix A : Figures
- Appendix B : Investigation Logs
- Appendix C : Laboratory Test Results
- Appendix D : Liquefaction Assessment Outputs
- Appendix E : Historical Aerial Photographs

1

1 Introduction

1.1 General / Scope

Tonkin & Taylor Ltd (T+T) was engaged by Halcyon Project Management on behalf of Napier City Council (NCC) to undertake geotechnical investigations and provide a geotechnical interpretive report for the proposed Napier Aquatic Centre (NAC). The proposed NAC site is adjacent to the Prebensen Drive Roundabout between SH2B and Tamatea Drive.

The works have been undertaken in accordance with our proposal dated 13 April 2018¹, which was accepted by the client on 4th May 2018².

Our scope of works has included:

- Review of publically available information including historical aerial photography, available historical geotechnical investigations and information held in the T+T archives;
- Ground investigations at the preferred Prebensen Drive site comprising 3 No sonic machine boreholes and 9 No CPTs.
- Installation of a single Piezometer in one of the boreholes to monitor groundwater levels on site;
- Preparation of summary borehole logs, site investigation plans and geological cross sections;
- Laboratory testing schedule to assist in liquefaction and consolidation settlement estimates comprising;
 - 2 No Atterberg limits tests
 - 3 No Particle Size Distribution tests;
 - 1 No Consolidation test.
- Undertake a liquefaction assessment based on the CPT and laboratory testing;
- Assess foundation options for the chosen site and indicate likely ground improvements that may be required; and
- Preparation of this report outlining the results of the investigations and analyses undertaken, along with the geotechnical considerations that will need to be addressed during the detailed design of the proposed aquatic centre.

We understand this report is to support a design and build contract.

¹ T+T, Offer of Geotechnical Services-Geotechnical Investigations and Assessment for land adjacent to the Cross-Country Drain in Napier, 22 November 2016, T+T ref: 1001268

² Signed acceptance, Rodney Howard (client Rep), 4 May 2017

2

1.2 Site Description

The site is legally described as “398 Prebensen Drive, Napier” Lot 2 DP 420058 with an area of approximately 12.2 Ha. The investigation was limited to the northern portion of site adjacent to the corner of Prebensen Drive and Tamatea Drive. The northern portion of the site was previously used for agricultural purposes and contained two residential dwellings which have since been demolished. A series of boardwalks (timber and steel) are currently being stored onsite within the area of the previously demolished residential dwellings.

The site is bounded by Tamatea Drive to the west, Prebensen Drive to the north, the SH50 Expressway to the east and undeveloped land to the south. The site is bounded by a drainage channel to the east with slopes up to 3m high at a grade of approximately 1V:2H.



Figure 1.1- Looking north towards Prebensen Dr, with the proposed site in the foreground.



Figure 1.2-Looking east from the site of the previously demolished residential dwellings.

3

1.3 Proposed development

We understand NCC intend to construct a new aquatic centre at the site including a 25m lane pool (with room for expansion to 50m) and associated gym and office facilities. At the time of writing this report, no development plans or architectural drawings were provided.

2 Desktop Review

2.1 Historical Aerial Photography

The earliest readily available aerial photograph from 1972 indicate the site was used as agricultural land with a small farmhouse still visible in the centre of the site. A series of farm tracks run in a north south and SW-NE direction that are still present on site.

The large drain on the eastern side of the site appears to run roughly north south along the site boundary.

A small ancillary shed is visible on the eastern portion of the site in the 1972 and 1980 aerial photos but appears to have been demolished by 1996.

Prior to 1988, a dog racing track was constructed just south of the proposed aquatic centre site with the development of a through road from Prebensen Drive towards Tamatea to the southwest.

Between 1996 and 2018 the site appears to have remained in roughly the same format. The old farmhouse building appears to have been partially demolished (circa 2012) with only the concrete block walls and foundations present on site.

Prebensen Drive was realigned between 2002-2003 and no longer passes through the site. This now forms Tamatea Drive to the west of the site.

The aerial photography review indicates that no significant filling operations appear to have taken place on site.

The relevant aerial photographs have been appended (Appendix E) to this report.

4

2.2 Published geology

Published geology³ indicates the site is underlain by Holocene estuarine deposits (Q1a), comprising unconsolidated mud, sand and peat. The published geology is shown in Figure 2.1 below.




Figure 2.1-Published geology of the Napier area.

2.3 Historical Geotechnical Investigations

A number of historical CPT tests have been pushed on site or the adjacent site. These include:

- A series of CPTs pushed across the Prebensen Drive Roundabout in 1989, northeast of the site.
- One CPT pushed on the eastern boundary of the site by Works Consultancy Services (Now WSP OPUS in 1995) for the Airport to Taradale Road upgrade.
- One CPT pushed by T+T in 2015 on the northeast of the site for Napier City Council to provide additional investigations for region liquefaction hazard maps.

3 Geotechnical Investigations (T+T 2018)

3.1 Site Investigations

Site investigations were undertaken between May and June 2018 and comprised the following:

- 9 No. CPTs pushed to 25m depth or refusal; and
- 3 No. machine boreholes to approximately 15m depth.

Borehole and CPT investigations were carried out by Geotech Drilling Ltd using a sonic drilling rig and a truck mounted CPT rig.

³ Lee, J.M; Bland, K.J; Townshend, D.B; Kamp, P.J.J. (compilers) 2011, Geology of the Hawkes Bay area, Institute of Geological and Nuclear Sciences 1:250 000 geological map 9.1 sheet +93 p. lower Hutt, New Zealand

5

The investigations outlined were supervised by an engineering geologist from T+T. In situ Standard Penetration Testing (SPT) was carried out at regular (1.5 m) intervals through the soil horizon as directed by the engineering geologist. The recovered drill core was photographed and logged to NZGS 'Field Description of Soil and Rock' guidelines.

On completion of the drilling one standpipe piezometer was installed in BH3 to monitor groundwater levels.

The investigation locations are shown on the investigation plan (Figure 1 in Appendix A) while the investigation logs are presented in Appendix B. Summary borehole details are presented in Table 3.1 below.

Table 3.1: Machine Borehole Summary

BH ID	Location (Hawkes Bay 2000)		Collar Elevation ¹ RL (m)	Total Depth (m)
	Easting (m)	Northing (m)		
BH1	817054.7	417075.0	11.95	15.45
BH2	817061.8	416961.9	11.78	15.15
BH3	816996.6	417041.1	11.82	15.45

¹Collar elevation surveyed by Civil Services (HB) Ltd (June 2018) and is in terms of Napier 1962 vertical datum.

3.2 Laboratory Testing

Select samples retrieved during the geotechnical investigation were tested by an IANZ accredited laboratory run by Opus International Consultants Ltd and Geotechnics Ltd. The purpose of the laboratory testing was to assist in characterising the subsoils encountered during the investigations and to assist in identifying the material susceptible to liquefaction and consolidation settlement.

The following tests were carried out:

- 1 No. 1 D consolidation settlement test;
- 2 No. PSD (Particle Size Distribution) tests;
- 2 No. Plasticity Index for Soils (Atterberg Limits) tests.

The results of laboratory testing is presented in Appendix C and discussed in subsequent sections.

4 Subsurface Conditions

4.1 Site Stratigraphy

The subsurface materials encountered during the investigations are generally consistent with the published geology. A summary of the materials encountered during the investigations are as follows:

- **Fill/Topsoil**
A surficial layer ploughed topsoil material comprising sandy silt was encountered up to approximately 0.2 m thick. Uncontrolled fill material comprising sandy medium to coarse gravel was encountered in BH1 to 1.2 m depth.
- **Holocene Estuarine Deposits- Estuarine Interbedded Sand and Silt**
Underlying the topsoil/fill are interbedded layers of sand and silt with fragments of shell. Cone tip resistances, q_c , ranges between 0.5 MPa and 20 MPa. SPT 'N' values range between 0 and 15 indicating this material is very loose/soft to medium dense/stiff. A layer of very soft to soft

6

silt was encountered in the majority of the test locations at 2.5m that was 1.0-2.5m thick with q_c values of less than 0.5MPa.

On the southern and eastern portion of the site the base of the interbedded sand and silt unit was unproven and this has been delineated on Figure 1 of Appendix A

- **Holocene Alluvial Deposits- Limestone Gravel/Dense Sand (Northwestern corner only)**

In the northwestern portion of the site a unit of well graded sandy gravels, cobbles and sands was encountered. This unit appeared to comprise a significant amount of limestone and shells. The spatial extent of this unit was limited to the northwestern corner of the site only (CPT 3,7,8 and BH2).

A number of the CPT's refused in this layer with tip resistances, q_c , generally exceeding 25 MPa. SPT 'N' values >50 indicating this material is dense to very dense.

The geological units expected across the site are summarised in Table 4.1. Geological cross sections through the site are presented on Figures 2-3 in Appendix A.

Table 4.1: General site profile

Unit	Depth to top of layer (m begl)	Cone Resistance (MPa)	SPT 'N' Value
Fill/Topsoil	0 – 1.2m	2 – 20	-
Estuarine Interbedded Sand and Silt	0.05 – 1.2m	0.5 - 14 (occasional lenses of greater than 20MPa material)	0 – 15
Limestone gravel	10.5- 12.6 (Portion of the site only- Refer Figure 1- Appendix A)	>25	>50

4.2 Groundwater

One standpipe piezometer was installed within BH3. Groundwater within the piezometer was measured at approximately 2.0 m below existing ground level (begl). Groundwater was also recorded between 2.2 and 2.3 m begl in BH1 and BH2 respectively following the completion of drilling.

We note some tidal and seasonal fluctuations are expected in the groundwater levels.

For the purposes of our analyses (outlined in subsequent sections) we have adopted a groundwater level of 1.5 m begl. This is based on the results of the site investigations and from our experience on adjacent sites.

A summary of groundwater levels measured following the installation of the piezometer is presented in Table 4.2 below.

Table 4.2: Piezometer details

ID	Collar RL (m)	Screen depth (m begl)	Min. – Max. water level in standpipe	Number of measurements	Geological Unit over screened depth
BH3	11.82	3.6 – 6.6	RL +9.82 (2.0 begl)	1	Interbedded fine to coarse SAND and SILT

5 Geotechnical Considerations

5.1 General

The recommendations and opinions in this report are based on data from machine borehole and CPT investigations, laboratory test results and review of published information. The nature and continuity of subsoil away from site investigations are inferred but it must be appreciated that actual conditions could vary from the assumed model.

5.2 Seismic shaking hazard

5.2.1 Seismic site subsoil class

While the CPTs and boreholes were terminated before bedrock was encountered; published geology indicates the estuarine deposits encountered could be hundreds of metres thick. Accordingly, based on the strengths of the materials encountered during the investigations we consider the site be classified as **Class D – Deep or Soft Soil Site** in accordance with NZS 1170.5:2004.

5.2.2 Ground shaking hazard

T+T's seismic assessment has been undertaken in accordance with the recommendations in the NZTA Bridge Manual and the New Zealand Code of Practice NZS 1170.5:2004 to represent the following design performance requirements:

- **Ultimate Limit State (ULS)** – to avoid collapse of the structural system, and
- **Serviceability Limit State (SLS)** – to avoid damage that would prevent the structure from being used as originally intended without repair.

In addition to the ULS and SLS cases above, a third design case has been assessed, being the 100 year recurrence interval (100y RI).

We have assumed structures associated with the proposed aquatic centre development are likely to be **Importance Level 3** in accordance with AS/NZS1170.0:2002, accordingly, the design earthquakes for serviceability and ultimate limit states have been adopted as 1 in 25 years and 1 in 1000 years respectively.

Table 5.1 presents the return periods for earthquakes with various 'unweighted' peak ground accelerations (PGA) with a corresponding earthquake magnitude.

Table 5.1: Ground seismic hazard

NZS 1170.5 Limit State	PGA (g)	Effective magnitude M_{eff}	Return period (years)
Ultimate limit state (ULS)	0.43	6.9	1000
100 Year Recurrence Interval (100y RI)	0.17	6.2	100
Serviceability limit state (SLS)	0.08	6.2	25

Note:

PGA and effective magnitude has been assessed based on Bridge Manual SP/M/022 Third Edition for the following:

Assumed design life of proposed structures 50 years

Assumed importance level of proposed structures 3 (NZS 1170.0:2004, Table 3.2)

Return period factor, R_u 1.3 for 1000yr; 0.5 for 100yr; and 0.25 for 25yr return period (NZS 1170.5:2004, Table 3.5)

Subsoil class D (Deep soil) – refer Section 3.1

8

Return period PGA coefficient, $C_{0,1000}$	0.43 (Bridge Manual Table 6A.1)
Site subsoil class factor, f	1.0 (Bridge Manual Section 6.2)
PGA	$C_{0,1000} \times R_u / 1.3 \times f \times g$ (Bridge Manual Section 6.2)
Effective Magnitude, M_{eff}	6.9 for 1000yr and 6.2 for 100yr and 25yr return period (Bridge Manual Table 6A.1)

5.3 Liquefaction assessment

When loose, saturated, cohesionless soils are subjected to strong shaking they have a tendency to try to densify. This tendency to densify results in excess pore pressures being generated and the soil undergoing partial to near-complete loss of shear strength. Such a loss of shear strength can result in, bearing capacity yield or failure, and/or horizontal movement of the soil mass. Release of the pressure to the surface can cause sand boils and settlement.

The occurrence of liquefaction is dependent on several factors including: the intensity and duration of ground shaking, soil density, particle size distribution, and elevation of the groundwater table.

5.3.1 Liquefaction susceptibility

Liquefaction only occurs in some soils. Liquefaction susceptible soils are typically saturated and non-cohesive.

- Sands and low plasticity and non-plastic silts are most susceptible to liquefaction⁴;
- Gravels can liquefy if they have a low permeability or are confined by less permeable layers. This is considered unlikely at the Prebensen Drive site;
- Some fine grained soils may be susceptible (typically low plasticity and high water content)^{5,6}. Bray and Sancio (2006) indicated that soils with plasticity index (PI) greater than 12 are unlikely to liquefy (as they behave in a cohesive manner) under seismic loading; and
- Younger (Holocene) deposits (present in Napier) are likely to be more susceptible to liquefaction than older (Pleistocene) deposits of similar composition, i.e. the age of the deposits is important.

5.3.2 Liquefaction potential

Analyses have been undertaken on CPTs to assess the potential of the subsoils for earthquake induced liquefaction. Analyses have been performed using 'unweighted' PGA with a corresponding Magnitude (refer to Section 5.2.2). The results of the laboratory testing outlined in Section 3.2 were used to calibrate the CPT based analyses.

From the analyses, the liquefaction potential at the site is summarised as follows:

SLS, 1/25 Return Period	Liquefaction is not expected.
100y IR, 1/100 Return Period	Triggering of liquefaction is expected, with liquefaction of interbedded sand layers expected between 4-6m and below 7m depth.
ULS, 1/500 Return Period	Liquefaction of interbedded sand layers expected between 2-3m and below 5m depth.

⁴ Bray, K et al, 2014, "Liquefaction effects on buildings in Central Business District of Christchurch", Earthquake Spectra, 30 (1), 85-109.

⁵ Bray J.D. and Sancio R.B., 2006, "Assessment of the liquefaction susceptibility of fine-grained soils", Journal of Geotechnical and Geoenvironmental Engineering, 132 (9), 1165-1177.

⁶ Boulanger R.W. and Idriss I.M., 2006, "Liquefaction Susceptibility Criteria for Silts and Clays", Journal of Geotechnical and Geoenvironmental Engineering, 132 (11), 1412-1426.

5.3.3 Consequences of Liquefaction

Free field settlement:

Liquefaction induced, one dimensional vertical reconsolidation settlements have been estimated using the methodology developed by Zhang, Robertson and Brachman (2002) and are presented in Table 5.4 below

It should be noted that estimated settlements are total, "free-field" settlement estimations. This describes the liquefaction induced settlement of the ground surface ignoring soil-structure interaction, which is caused by a dissipation of excess pore water pressure generated during earthquake shaking. The settlement of the proposed structures may differ from the estimated ground settlement and is dependent on the interaction of the building and soil it is founded on.

LSN:

The Liquefaction Severity Number (LSN) is another indicator of the effects liquefaction can have on land and shallow foundations. LSN was developed from observations of residential damage from the Canterbury Earthquake Sequence and its calculation is presented below:

$$LSN = \int \frac{\epsilon_v}{z} dz$$

Where ϵ_v is the calculated volumetric densification strain using Idriss and Boulanger (2014) and z is the depth to the layer of interest.

As the LSN increases, so does the risk of adverse ground level effects associated with liquefaction. Table 5.2 summarises correlations of LSN with land and residential building damage, as observed from the Canterbury Earthquake Sequence.

Table 5.2: LSN ranges and associated damage

LSN Range	Effects and Expression of Liquefaction on Structures and Land
0-5	Negligible to Minor: No major effects expected.
5-20	Minor: Generally consistent with acceptable performance under SLS conditions (i.e. little settlement or permanent dwelling damage). Some ejection of material can be expected at the ground surface, but likely to be localised in nature.
20-40	Moderate: Liquefaction evidence possible. Generally consistent with acceptable performance under ULS conditions (i.e. settlement).
>40	Severe: High risk of substantial damage to the site and/or building if on shallow foundations

5.3.4 Lateral Spreading

Lateral spread is the movement of ground down slope or toward a free edge (e.g. drainage channel) as a result of shearing of weak liquefied ground under seismic and/or gravity forces. Lateral spread could be expected to occur in a series of surface cracks and fissures extending back from the channel edge with the magnitude of total displacement reducing with distance from the reclamation edge. With increasing magnitude and acceleration of earthquakes, greater displacement and greater extent of lateral spread can be expected.

Generally, the risk of lateral spreading decreases with distance from the free face (L). The risk regions for lateral spread in relation to the development can be summarised as follows:

1. **L = 0 – 5H 'Edge failure Region'**, where H is the height of the free face. Significant ground cracking, large horizontal and vertical displacement displacements and ground failure can

10

occur. Building in this zone without significant ground improvements or suitably detailed piles is not recommended;

2. **L = 5 – 20H 'Block sliding Region'** - Block Slide zone here the lateral spreading displacement could be concentrated over one or two large cracks as large blocks of soil slide towards the stream. In this region, robust shallow foundations (stiffened raft type) should be detailed to resist the strains from the ground trying to "pull apart", possibly in combination with some ground improvements; and
3. **L > 20H 'Lateral stretch Region'** - here the lateral spreading displacement occurs over a large number of small cracks, gradually decreasing in width with increasing distance from the stream. These cracks generally have a minor influence on structural performance.

Estimated lateral spread displacements are presented in Sections 5.3.5 and 5.3.6 below. The above regions are independent of the risk zones shown in Figure 2, Appendix A.

5.3.5 Discussion

Our liquefaction assessment indicates that there is moderate risk of liquefaction under a ULS event and minor to moderate liquefaction risk in a 1 in 100 year event. A 1.5-1.8m crust of 'non-liquefiable materials' appears to be present at the site based on the CPTs, lab testing and groundwater measurements. There appears to be a negligible change in liquefaction risk between an IL2 and IL3 design level event.

Pool:

Assuming that the pool is to be constructed by excavating below existing ground level and in the western portion of the site (green zone on Figure 2 in Appendix A), an approximately 3m deep excavation would effectively remove the shallow potentially liquefiable material encountered on site. We expect the soft to firm plastic clayey silt later from 2.5-5.0m depth will provide an impermeable barrier from liquefaction at depths greater than 6m.

The pool would then found on the non-liquefiable silts underlying the upper liquefiable sands lenses. While analyses indicate the silts are not susceptible to liquefaction, they may be susceptible to cyclic softening (i.e. a temporary reduction in undrained shear strength as result of seismic loading). An assessment of the effects of temporary strength loss on structural performance should be undertaken during detailed design.

Building:

Building foundations along the perimeter of the site will need to be designed to prevent excessive liquefaction damage under 1 in 100 year and ULS events. Shallow ground improvements such as geogrid reinforced gravel rafts or in situ/ex situ cement stabilisation are likely to be appropriate liquefaction damage mitigation methods. In addition it is recommended foundations are tied together to prevent the structure "pulling apart" under seismic loading.

The liquefaction analysis will need to be reassessed during detailed design following confirmation of cut/fill levels.

The CPT based liquefaction assessment outputs are provided in Appendix of this report.

Non-uniform liquefaction damage is expected across the site. For reporting purposes, the site has been divided into three zones based on expected consequences of liquefaction of underlying soils and potential risk mitigation strategies. Figure 2 in Appendix A illustrates the spatial locations of each zone.

11

Results of the liquefaction assessment indicate the consequences of liquefaction and (as a result lateral spread) are expected to be greater in Zones 1 and 2 than those in Zone 3 (due to the presence of the open drain). Accordingly, it is recommended that the swimming pool is located in Zone 3 and Zones 1 and 2 used for carparking.

Table 5.3 summarises liquefaction consequences for each zone.

Table 5.3: Liquefaction consequences

Issue	Zone 1	Zone 2	Zone 3
Estimated free field settlement ¹	ULS event: 100-120mm 100y RI: 60-80mm	ULS event: 100-140mm 100y RI: 60-120mm	ULS event: 50-120mm 100y RI: 40-100mm
Sand boils ²	ULS event: Expected 100y RI: Possible	ULS event: Expected 100y RI: Possible	ULS event: Expected 100y RI: Possible
Surface Damage, based on LSN ³	ULS event: Moderate 100y RI: Moderate	ULS event: Minor-Moderate 100y RI: Minor- Moderate	ULS event: Minor- Moderate 100y RI: Minor
Lateral spread ⁴	ULS event: Expected 100y RI: Expected	ULS event: Expected 100y RI: Possible	ULS event: Unlikely 100y RI: Unlikely
Lateral stretch ⁴	ULS event: Expected 100y RI: Expected	ULS event: Expected 100y RI: Possible	ULS event: Unlikely 100y RI: Unlikely

Note:

- 1 Refer to Section 5.3.3 above.
- 2 Sand boils occur when liquefied soils at depth break through to the ground surface through fissures, cracking and/or weak crustal soils.
- 3 LSN (Liquefaction Severity Number), refer to Section 5.3.3 above.
- 4 Refer to Section 5.3.6 below

12

Table 5.4 summarises predicted lateral spread within each “zone” for various levels of earthquake shaking, assuming existing, non-improved ground conditions.

Table 5.4: Expected lateral spread

Zone	Expected (Possible) Lateral Spread ¹	
	ULS	100 year RI
Zone 1 –Within 20m of the free face	Up to 2m	Up to 600mm
Zone 2 - (20 m – 40 m from free face) + CPT03	Up to 600 mm	Up to 300 mm
Zone 3 - (> 40 m – from free face)	This zone is not likely to be subject to large lateral spread displacements. However, small cracks decreasing in width (with increasing distance from the stream) may develop.	

Note:

The lateral spread estimations above are for the boundary closest to the drainage channel. The estimations are based on empirical analyses developed from historical observations. We would not expect actual lateral spread to fall outside the “possible” range but we cannot discount this.




Figure 5.1: Lateral Displacement Profile –ULS case

Lateral stretch is defined as the difference in lateral spread (displacement) over a given length, perpendicular to the free face (drainage channel), effectively lateral strain within the ground. Lateral stretching of the ground is anticipated following an ULS earthquake event, with the majority of lateral stretch occurring within Zone 1 closest to the drain. Table 5.5 summarises predicted lateral stretch within each zone for various levels of earthquake shaking, being ULS and 100 year RI.

13

Table 5.5: Expected lateral stretch

Zone	Expected Lateral Stretch (mm)	
	ULS	100 year RI
Zone 1 – Within 20m of free face	Up to 1000mm	Up to 350mm
Zone 2 - (20 m – 40 m from free face) + CPT03	Up to 200 mm over 10m length	Up to 100 mm over 10m length
Zone 3 - (> 40 m – from free face)	Up to 50 mm over 10m length	Negligible




Figure 5.2: Lateral stretch profile-ULS case

5.4 Consolidation Settlement

Settlement calculations were performed on the results of CPT data using software program *Settle 3D*. The purpose of the calculations was to estimate primary consolidation settlements that may result from earthworks (filling) and future building and pavement loads.

The results of 1D consolidation tests were used to confirm the settlements derived from CPT data. Our assessment has been based on assumed loads and layouts as these were not available at the time of writing.

Based on our experience in the area we expect the majority of settlements to occur relatively quickly, due to the presence of interbedded sand layers which provide drainage pathways.

Estimated settlements based on a range of loads are provided in Table 5.6 below:

Table 5.6: Range of consolidation settlements based on loads

Applied Load	Estimated settlements
10kPa	20-40mm
20kPa	50-80mm
30kPa	50-120mm

We note that a pool excavation may “compensate” the loads from the pool by the removal of soil overburden. However this will need to be assessed following confirmation of excavation depths.

Differential settlement between the pad foundations will need to be reassessed during detailed design following confirmation of design loads and layout. If site levels are raised (to mitigate flooding etc.) this will impart additional surcharge on the ground and consolidation settlement, estimates should be reviewed on development of building and site plans.

If significant site filling is required, “pre loading” may be considered to mitigate the risk of consolidation settlements on future structures and services. “Pre loading” involves the placement of a surcharge load (typically additional fill) in order to simulate building loads and for the majority of expected consolidation settlement to occur prior to construction.

5.4.1 Settlement monitoring

Depending on the final cut/fill levels there may be a requirement to pre load the site and monitor the resulting settlements. This will need to be confirmed during detailed design.

Settlement of any new structural fill placed on site should be monitored for a period of at least 3 months to confirm the design assumptions regarding settlement magnitude and suitability for construction of structures/services, as mentioned in Section 5.5. We recommend that settlement plates are installed within any new fill placed on each Lot to monitor consolidation settlements.

Settlement monitoring results should be provided to T+T to determine if consolidation settlements have ceased. If settlements are ongoing the fill may require addition time to settle or could be surcharged with additional fill to increase the rate of settlement.

5.5 Foundation Considerations

5.5.1 Zone 1 Foundations

Analyses indicates that ground improvement would be required for structures and services constructed within Zone 1 to limit lateral spread/stretch risk. These options could comprise the following (subject to detailed design):

- Soil-cement mixed columns (DSM);
- Stone Columns (Vibroflot); and
- Rammed Aggregate Piers (RAPs)

Further details of these options will need to be following confirmation of preferred site layouts.

5.5.2 Zone 2 Ground Improvement and Foundations

For foundations within Zone 2 (i.e. within 40 m of the drain free edge) we recommend ground improvement measures are implemented to stiffen the founding ground to mitigate the effects of

15

lateral spread within the zone and to allow the construction of shallow foundations. Ground improvement and foundation options in Zone 2 could comprise:

- 1.2 m thick geogrid reinforced gravel rafts, with stiffened rafts (as per Zone 3). This would involve placement and compaction of crushed, angular gravel in approximately 200 mm thick layers. The gravel should be reinforced with geogrid with 40kN/m minimum tensile strength at 5% elongation, with the grid placed 200 mm and 400 mm from the base of the raft. The grid should be lapped at joins as specified by the manufacturer; or
- Perimeter treatment (DSM, RAPs or Stone Columns) to a minimum depth twice the height of the free face. As per the recommendations for Zone 1 above, perimeter treatment details will need to be developed during detailed design if required.

5.5.3 Zone 3 Foundations

5.5.3.1 Shallow foundations

Foundations within Zone 3 are not considered to be at a major risk of lateral spread/stretch damage. However, foundations in this area will need to account for both consolidation and liquefaction induced settlements. Depending on acceptable risk and tolerances to consolidation and liquefaction induced settlements, ground improvements may be required.

We expect that foundations in Zone 3 could comprise shallow raft foundations with interconnected ground beams. A 0.8-1.0m thick engineered granular fill raft below foundation level could be constructed to support foundations in this zone to mitigate the effects of liquefaction induced settlements if the risk is considered unacceptable.

The gravel rafts should include at least 2 layers of high tensile geogrid to stiffen the raft. A layer of geofabric (Bidum A19 or similar) should be placed at the base of any excavation to prevent punching failures during compaction and aid in separation of the engineered fill from the subgrade.

Alternatively, a 1.5m thick in situ cement stabilised raft could be constructed to form a stabilised crust under the perimeter of the building.

5.5.3.2 Pile Foundations

Due to the inconsistency of the dense limestone gravel layer across the site (refer highlighted area on Figure 1-Appendix A) a deep piled solution within the area where gravels were encountered (as indicated on Figure 1 in Appendix A) may be suitable. However, further investigation is recommended to prove the consistency of this layer.

5.5.4 Services

It is recommended that critical services be located outside the spread zone i.e. further than 40 m from the drain free face (unless ground improvements are undertaken). We note that a series of main trunk water mains run along the southern and eastern boundaries of the site.

Services in Zone 2-3 should be designed to be flexible to accommodate up to 100mm of vertical settlement during a 1 in 100 year seismic event.

5.6 Earthworks Considerations

5.6.1 General

The site should be cleared of vegetation and all existing fill (up to 1m deep) and topsoil should be stripped from the cut and fill areas. An inspection should be carried out of all stripped areas prior to filling or cutting operations commencing.

16

5.6.2 Structural Fill

Compaction of new fill material should be in accordance with the normal requirements of NZS 4404:2010 and should be the subject of engineering earthwork trials prior to bulk earthworks taking place.

We recommend that the compaction characteristics of any proposed fill material are obtained to ensure that they are suitable for use.

Typical performance specifications for granular fill and cohesive fill are outlined below, however should be reviewed once fill sources are confirmed:

Granular Fill

- Average of 95% Maximum Dry Density (MDD) – standard compaction;
- No result less than 92% MDD; and
- Clegg impact value – No result less than 20 CIV (or as determined from field trials).

Cohesive Fill

- Shear strengths (measured in situ with a hand held shear vane)- average of 140kPa;
- Shear strengths- No result less than 120kPa;
- Average 8% - maximum air voids; and
- No individual result greater than 10% air voids.

From experience on neighbouring sites the local “straight haul” gravels, mixed with local silts are likely to be suitable for use on site, provided they are compacted in accordance with the specifications above, and water content is well controlled. This would not be the case in Zone 2, where crushed angular gravels would be required for the construction of shallow gravel raft ground improvements.

6 Pavement Design

Our experience on the neighbouring sites indicates that the underlying sands and silt are predominantly of low strength. Based on our experience, a CBR of 2% would be appropriate for light weight pavements at the subject site.

During excavation of the pavement areas, the subgrade should be inspected by a geotechnical engineer to assess any areas that may require undercutting and replacement with compacted hardfill. Alternatively a cement stabilised subgrade could be adopted.

Following stripping of the topsoil, the trafficability of the site soils may be expected to deteriorate, especially following wet weather. It is imperative that the exposed surfaces are not disturbed and sensitive soils are not subject to remoulding. We recommend tracked vehicles only be allowed to pass over roading areas in these conditions, as wheeled vehicles may cause the subgrade to fail and hence require over-excavation, and (possibly removal of the subgrade to spoil or to stockpile for drying and re-working) to be required.

Following confirmation of site layouts a series of Scala penetrometer tests should be undertaken to confirm CBR values for design.

17

7 Retention Design and Groundwater Control

If an excavation is required for the swimming pool, the geotechnical parameters in Table 7.1 are considered suitable for use in preliminary retention design (sheet piling etc.). The earth pressure coefficients do not account for wall friction.

Table 7.1: Retention design parameters

Unit	Effective Friction Angle (ϕ')	Unit weight (γ), kN/m ³	Effective Cohesion (kPa)	At rest earth pressure coefficient (k_0)	Active earth pressure coefficient (k_a)	Passive earth pressure coefficient (k_p)
Sand	30	18	0	0.50	0.33	3.00
Silt	26	17	2	0.56	0.39	2.56

Allowance should be made in the retaining wall design for groundwater pressures, surcharge loading of the retaining wall due to stockpiles and/or construction traffic and the potential liquefaction of bands of soil within the retained soil profile.

A geotechnical ultimate bearing capacity of 150kPa may be assumed for the design of any retaining wall footings bearing on soft alluvial silts. A strength reduction factor of 0.5 should be applied for the ULS design case.

An allowance for buoyancy pressures on the pool superstructure will need to be allowed for in design when the pool is emptied for periodic maintenance.

18

8 Conclusions and Recommendations

Geotechnical investigations and reporting have been completed for the proposed aquatic centre at Prebensen Drive, Parklands, Napier. The following points summarise the main conclusions of the investigation and results of engineering analysis.

- 1 A 25m lane pool complex is proposed on the vacant lot between Prebensen Drive, Tamatea Drive and the Hawkes Bay Expressway-At this time no site layouts and architectural plans are available;
- 2 Aerial photography indicates the site has previously been used as agricultural land with a former farmhouse present on the southern area of the site until 2012, the remnants of the dwelling foundations are still exposed on site. No evidence of site filling was evident from review of the aerial photographs;
- 3 The site is underlain by Holocene estuarine deposits comprising interbedded layers of sand and silt with fragments of shell. A soft silt layer is present at 2.5-5.0m depth. A dense gravel layer is present on a portion of the site only at 10-15m depth (shown on Figure 1);
- 4 We consider the site should be classified as Class D – Deep or Soft Soil Site in accordance with NZS 1170.5:2004;
- 5 The site is subject to the following geotechnical risks;
 - Liquefaction during a 100 year RI (at which some liquefaction triggering occurs) and an ULS earthquake event;
 - Lateral spreading following liquefaction, within the zones closest to the open drain to the east of the site (Zones 1 and 2 on Figure 2 in Appendix A);
 - Consolidation settlement with ranges of estimated settlements presented in Section 5.4
- 6 For reporting purposes the site has been separated into 3 Zones (refer Figure 1 in Appendix A) based on expected performance with regard to liquefaction and lateral spread;
 - Significant Ground improvements are recommended in Zones 1- 2 to limit the effects of lateral spreading on proposed structures.
 - Zone 3 is not expected to be at significant risk of lateral spreading and only shallow ground improvements likely to facilitate development of shallow foundations.
Accordingly we recommend the pool be situated in this zone.
- 7 A CBR of 2% is considered appropriate for pavement design on site, this should be confirmed with Scala penetrometer testing during detailed design;
- 8 Preliminary retention design parameters are presented in Section 7; and
- 9 Further geotechnical analyses will be required during detailed design once site layouts and levels have been confirmed.

19

9 Applicability

This report has been prepared for the exclusive use of our client Napier City Council Limited, with respect to the particular brief given to us and it may not be relied upon in other contexts or for any other purpose, or by any person other than our client, without our prior written agreement.

The susceptibility analyses carried out are based on empirical methods derived from case histories/databases with limited information. Earthquakes are unique and impose different levels of shaking in different directions on different sites. The results of the liquefaction susceptibility analyses and the estimates of consequences presented within this document are based on regional seismic demand and published analysis methods, but it is important to understand that the actual performance may vary from that calculated.

During excavation and construction, the site should be examined by an engineer competent to judge whether the exposed subsoils are compatible with the inferred conditions on which the report has been based. We would be pleased to provide this service to you and believe your project would benefit from the continuity. However, it is important that we be contacted if there is any variation in subsoil conditions from those described in the report

Tonkin & Taylor Ltd

Report prepared by:



Jamie Yule/John Martin
Engineering Geologist/ Geotechnical Engineer

Reviewed for Tonkin & Taylor Ltd by:



Nathan Hickman
CPEng Geotechnical Engineer


Authorised for Tonkin & Taylor Ltd by:



for Grant Loney
Project Director


p:\1006598\workingmaterial\report\1006598_geotechnical report_joma_v2.docx


Appendix A: Figures

- Figure 1 – Site Investigation Plan
- Figure 2- Liquefaction and Lateral Spread Hazard Plan
- Figures 3-4 – Geological Cross Sections











Appendix B: Investigation Logs

- Borehole Logs
- CPT Logs

 Tonkin+Taylor		BOREHOLE LOG										BOREHOLE No.: BH01	
PROJECT: Napier Aquatic Centre JOB No.: 1006598 LOCATION: Eastern side of site, near drain feature.		CO-ORDINATES: 417075.00 N (HA/WKTM2000) 817054.70 E		R.L. GROUND: 11.95m R.L. COLLAR: DATUM: NAPIHT1962		SURVEY: Total Station Surveyed						SHEET: 1 OF 2 DRILLED BY: Matt LOGGED BY: JWW CHECKED: ADP START DATE: 23/05/2018 FINISH DATE: 23/05/2018 CONTRACTOR: Geotech Drilling	
DIRECTION: ANGLE FROM HORIZ.: -90°		Rock Weathering Rock Strength Sampling Method Core Recovery (%)		Testing RL (m) Depth (m)		Graphic Log Defect Log Fracture Spacing (mm)		ROCK DEFECTS Description & Additional Observations		Fluid Loss (%) Water Level Casing Installation Core Box No			
GEOLOGICAL UNIT SOIL: Classification, colour, consistency / density, moisture, plasticity ROCK: Weathering, colour, fabric, name, strength, cementation													
Fill	No recovery 0-0.8m												
	Sandy medium to coarse GRAVEL, minor cobbles; dark greyish brown. Tightly packed, dry, well graded.												
Estuarine	Fine SAND, trace silt; dark brown. Loose, moist, uniformly graded.												
	Fine SAND, minor silt; dark bluish grey. Loose, wet, uniformly graded, lenses of soft sandy silt interbedded throughout												
	SILT, some clay; dark bluish grey. Very soft to soft, wet, moderate to high plasticity.												
	Fine SAND, some fine to coarse shell fragments, minor silt, trace clay; dark grey. Loose, wet, well graded.												
	Fine SAND, minor silt, trace shell fragments; dark grey. Loose, wet, slightly dilatant.												
	Sandy SILT; dark bluish grey. Firm, wet, low plasticity.												
	Silty fine SAND; dark grey. Loose, wet, uniformly graded.												
	SILT, some clay; dark greenish grey. Soft to firm, wet, low to moderate plasticity.												
	Silty fine SAND; dark grey. Very loose to loose, wet, uniformly graded.												
	Sandy SILT; dark greenish grey. Very soft to soft, wet, low plasticity.												
9.65 - 9.90m: Silty sand lense 250mm thick													

COMMENTS:
 Hole Depth 15.45m
 Scale 1:50


Rev. 1: 0.5-1.5m
 Rev. 2: 3.5-5.5m
 Rev. 3: 6.5-8.5m

 Tonkin+Taylor		<h2 style="text-align: center;">BOREHOLE LOG</h2>										BOREHOLE No.: <h1 style="text-align: center;">BH01</h1>						
PROJECT: Napier Aquatic Centre JOB No.: 1006598 LOCATION: Eastern side of site, near drain feature.		CO-ORDINATES: 417075.00 N (HAWKTM2000) 817054.70 E		R.L. GROUND: 11.95m R.L. COLLAR: DATUM: NAPIHT1962		SHEET: 2 OF 2 DRILLED BY: Matt LOGGED BY: JWY CHECKED: ADP START DATE: 23/05/2018 FINISH DATE: 23/05/2018 CONTRACTOR: Geotech Drilling												
DIRECTION: ANGLE FROM HORIZ.: -90°		SURVEY: Total Station/Surveyed																
GEOLOGICAL UNIT	DESCRIPTION OF CORE	Rock Weathering	Rock Strength	Sampling Method	Core Recovery (%)	Testing	RL (m)	Depth (m)	Graphic Log	ROCK DEFECTS				Fluid Loss (%)	Water Level	Casing	Installation	Core Box No
										Defect Log	Fracture Spacing (mm)	RQD (%)	Description & Additional Observations					
Estuarine	SOIL: Classification, colour, consistency / density, moisture, plasticity ROCK: Weathering, colour, fabric, name, strength, cementation																	
	Silty fine SAND, trace organics in thin discrete lenses; dark grey. Loose, wet, uniformly graded. 10.65 - 10.85m: Silt lense 200mm thick			SNC	100			11										
				SPT		0/0 0/1 1/2 N=4												
	12.00m: becomes medium dense			SNC	100			12										
				SPT		1/2 3/3 2/2 N=10												
	12.45 - 12.65m: Silt lense 200mm thick			SNC	100			13										
				SPT		1/0 0/1 3/3 N=7												
	13.20m: becomes loose			SNC	100			14										
				SPT		2/3 2/2 2/3 N=9												
	14.15 - 14.25m: thin silt lense			SNC	100			15										
14.65 - 14.75m: thin silt lense			SPT															
15.45m: Target depth																		

General Log - 1205/2018 9:20:53 a.m. - Produced with Core-OS by Geillio

COMMENTS:
Hole Depth: 15.45m
Scale 1:50

Rev: A

 Tonkin+Taylor		BOREHOLE LOG				BOREHOLE No.: BH02											
PROJECT: Napier Aquatic Centre JOB No.: 1006598 LOCATION: Northern portion of site		CO-ORDINATES: 416961.90 N 817061.80 E (NAPIHTM2000) DIRECTION: ANGLE FROM HORIZ.: -90°		R.L. GROUND: 11.78m R.L. COLLAR: DATUM: NAPIHT1962 SURVEY: Total Station/Surveyed		SHEET: 1 OF 2 DRILLED BY: Matt LOGGED BY: JWY CHECKED: ADP START DATE: 22/05/2018 FINISH DATE: 22/05/2018 CONTRACTOR: Geotech Drilling											
GEOLOGICAL UNIT	DESCRIPTION OF CORE	Rock Weathering	Rock Strength	Sampling Method	Core Recovery (%)	Testing	RL (m)	Depth (m)	Graphic Log	Defect Log	ROCK DEFECTS		Fluid Loss (%)	Water Level	Casing	Installation	Core Box No
											Fracture Spacing (mm)	ROD (%)					
SOIL: Classification, colour, consistency / density, moisture, plasticity ROCK: Weathering, colour, fabric, name, strength, cementation																	
Fill	Sandy Topsoil with rootlets																
	Fine SAND, minor silt; dark brown. Loose, moist, uniformly graded.																
	No recovery 1.05-1.5m																
	Fine SAND, minor silt and trace shell fragments; dark grey. Loose, wet, uniformly graded.																
	Clayey SILT; dark brownish grey. Very soft to soft, wet, high plasticity.																
	Shelly fine to medium SAND with some silt; dark grey. Loose, wet, well graded.																
	SILT, minor clay; dark greenish grey. Firm, wet, moderate to high plasticity.																
	Fine SAND, minor silt, trace organics; dark grey. Loose, wet, uniformly graded																
	Silty fine SAND, some shell fragments; dark grey. Loose, wet, uniformly graded.																
	Sandy SILT; dark grey. Soft, wet, low to moderate plasticity																
Estuarine	Silty fine SAND; dark grey. Loose, wet, uniformly graded.																


General Log - 1305/2018 2:20:53 a.m. - Produced with Core-OS by Geotech

COMMENTS:

Hole Depth: 15.15m

Scale 1:50

Rev: A


 TONKIN+TAYLOR		BOREHOLE LOG										BOREHOLE No.: BH02						
PROJECT: Napier Aquatic Centre JOB No.: 1006598 LOCATION: Northern portion of site		CO-ORDINATES: 416961.90 N (HAWKTM2000) 817061.80 E		R.L. GROUND: 11.78m R.L. COLLAR: DATUM: NAPIHT1962		SHEET: 2 OF 2 DRILLED BY: Matt LOGGED BY: JWY CHECKED: ADP START DATE: 22/05/2018 FINISH DATE: 22/05/2018 CONTRACTOR: Geotech Drilling												
DIRECTION: ANGLE FROM HORIZ.: -90°		SURVEY: Total Station Surveyed																
GEOLOGICAL UNIT	DESCRIPTION OF CORE	Rock Weathering	Rock Strength	Sampling Method	Core Recovery (%)	Testing	RL (m)	Depth (m)	Graphic Log	Defect Log	Fracture Spacing (mm)	RQD (%)	Description & Additional Observations	Fluid Loss (%)	Water Level	Casing	Installation	Core Box No
	SOIL: Classification, colour, consistency / density, moisture, plasticity ROCK: Weathering, colour, fabric, name, strength, cementation																	
Estuarine	Sandy SILT, trace clay and organics and shell fragments; dark brownish grey. Firm, wet, low plasticity.			SNC	100			0.0										
	Silty fine SAND, trace clay; dark brownish grey. Loose, wet, uniformly graded.			SPT		1/1		1										
Holocene Alluvial Deposits				SNC	100			11										
				SPT		1/1		12										
				SNC	100			13										
	Sandy fine to medium GRAVEL, some silt; light whitish grey. Very dense, wet, well graded. Gravels; limestone, subrounded.			SNC	100			14										
	No recovery of SPT sample			SPT		23/27 for 75mm N=50		15										
	Silty fine to coarse SAND, some gravel and minor cobbles; light brownish grey. Very dense, wet, well graded. Gravels/Cobbles; limestone, white and grey			SNC	88			16										
	15.15m: Target depth			SPT		28/22 for 45mm N=50		17										
								18										
								19										
								20										
								21										
								22										
								23										
								24										
								25										
								26										
								27										
								28										
								29										
								30										
								31										
								32										
								33										
								34										
								35										
								36										
								37										
								38										
								39										
								40										
								41										
								42										
								43										
								44										
								45										
								46										
								47										
								48										
								49										
								50										


General Log - 12/05/2018 9:20:53 a.m. - Produced with Core-CSS by Celltec


COMMENTS:
Hole Depth: 15.15m
Scale 1:50


Rev: A


66


 BOREHOLE LOG										BOREHOLE No.: BH03							
PROJECT: Napier Aquatic Centre JOB No.: 1006598 LOCATION: Centre south of the proposed site										SHEET: 2 OF 2 DRILLED BY: Matt LOGGED BY: NAH CHECKED: JWY START DATE: 23/05/2018 FINISH DATE: 23/05/2018 CONTRACTOR: Geotech Drilling Ltd							
CO-ORDINATES: 417041.10 N 816996.60 E (HAWKTM2000) DIRECTION: ANGLE FROM HORIZ.: -90°										R.L. GROUND: 11.82m R.L. COLLAR: DATUM: NAPIHT1962 SURVEY: Total Station\Surveyed							
GEOLOGICAL UNIT	DESCRIPTION OF CORE	Rock Weathering	Rock Strength	Sampling Method	Core Recovery (%)	Testing	RL (m)	Depth (m)	ROCK DEFECTS				Fluid Loss (%)	Water Level	Casing	Installation	Core Box No
									Graphic Log	Defect Log	Fracture Spacing (mm)	ROD (%)					
SOIL: Classification, colour, consistency / density, moisture, plasticity ROCK: Weathering, colour, fabric, name, strength, cementation																	
Estuarine	[CONT] Fine to coarse SAND, with some silt; grey. Loose, moist.			SNC	100			11									
				SPT		1/2											
				SNC	100												
				SPT		1/2											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		1/2											
				SNC	100												
				SPT		1/1											
	13.50m: grades medium dense.			SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												
				SPT		1/1											
				SNC	100												
				SPT		2/3											
				SNC	100												






















Appendix C: Laboratory Test Results

- 1 D Consolidation Settlement Test
- Atterberg limit and particle size distribution test results


WET SIEVE ANALYSIS TEST REPORT



Project : NCC Aquatic Centre
 Location : Napier
 Client : J. Yule, PO Box 5271, Auckland
 Contractor : Geotech Drilling
 Sampled by : Geotech Drilling
 Date sampled : 23/05/18
 Sampling method : Unknown
 Sample description : SILT with minor sand
 Sample condition : Tested as received
 Bore hole no : I
 Depth (m) : 4.5

Project No : 2-L0065.09
 Lab Ref No : NA 1717 A
 Client Ref No : 1006598

Sieve Analysis							
Size (mm)	% Passing	Size (mm)	% Passing	Size (mm)	% Passing	Size (mm)	% Passing
63.00	100	19.00	100	2.36	100	0.300	99
53.00	100	13.20	100	1.18	100	0.150	97
37.50	100	6.70	100	0.60	100	0.075	89
26.50	100	4.75	100	0.425	100	0.063	88



Test Method	Notes
NZS 4407 : 2015 Test 3.8.1	History: Ex BH 1 at 4.5m Fraction tested: Whole Dispersant Used: Nil <i>Fraction passing finest sieve is by difference.</i>

Date tested : 07/06/18

Date reported : 12/06/18

This report may only be reproduced in full

Approved

J Crichton

Designation : Assistant Laboratory Manager

Date : 12/06/18

PF-LAB-099 (20/03/2018)

Page 1 of 1

WSP Opus
 Napier Laboratory
 Quality Management Systems Certified to ISO 9001

90 Prebensen Drive
 Private Bag 6019, Hawkes Bay Mail
 Centre, Napier 4142, New Zealand

Telephone +64 6 833 5590
 Website www.wsp-opus.co.nz

PLASTICITY INDEX FOR AGGREGATES TEST REPORT
--



Project : NCC Aquatic Centre
 Location : Napier
 Client : J. Yule, PO Box 5271, Auckland
 Contractor : Geotech Drilling
 Sampled by : Geotech Drilling
 Date sampled : 23/05/18
 Sampling method : Unknown
 Sample description : Sandy SILT
 Sample condition : Tested as received
 Source : BH 1 at 1.5m

Project No :	2-L0065.09
Lab Ref No :	NA 1717B
Client Ref No :	1006598

Test Results	
Client Ref No :	1006598
Cone penetration limit :	34
Plastic limit :	NA
Plasticity index :	NP
Sample fraction :	That passing 425µm test sieve
Natural Water Content :	35.6%

Test Methods	Notes
Cone Penetration	NZS 4407 : 2015 : Test 3.2
Plastic Limit	NZS 4407 : 2015 : Test 3.3
Plasticity Index	NZS 4407 : 2015 : Test 3.4
	NA = Not attainable NP= Non plastic

Date tested : 11/06/18
 Date reported : 12/06/18

This report may only be reproduced in full

Approved 
 Designation : Assistant Laboratory Manager
 Date : 12/06/18

PF-LAB-053 (20/03/2018)

Page 1 of 1

WSP Opus
 Napier Laboratory
 Quality Management Systems Certified to ISO 9001

90 Prebensen Drive
 Private Bag 6019, Hawkes Bay Mail Centre,
 Napier 4142, New Zealand

Telephone +64 6 833 5590
 Website www.wsp-opus.co.nz


WET SIEVE ANALYSIS TEST REPORT



Project : NCC Aquatic Centre
 Location : Napier
 Client : J. Yule, PO Box 5271, Auckland
 Contractor : Geotech Drilling
 Sampled by : Geotech Drilling
 Date sampled : 23/05/18
 Sampling method : Unknown
 Sample description : SAND with minor silt
 Sample condition : Tested as received
 Bore hole no : 2
 Depth (m) : 1.95 - 2.2

Project No : 2-L0065.09
 Lab Ref No : NA 1717 C
 Client Ref No : 1006598

Sieve Analysis							
Size (mm)	% Passing	Size (mm)	% Passing	Size (mm)	% Passing	Size (mm)	% Passing
63.00	100	19.00	100	2.36	100	0.300	100
53.00	100	13.20	100	1.18	100	0.150	79
37.50	100	6.70	100	0.60	100	0.075	14
26.50	100	4.75	100	0.425	100	0.063	11



Test Method	Notes
NZS 4407 : 2015 Test 3.8.1	History: Ex BH 2 at 1.95 - 2.2m Fraction tested: Whole Dispersant Used: Nil <i>Fraction passing finest sieve is by difference.</i>

Date tested : 07/06/18

Date reported : 12/06/18

This report may only be reproduced in full

Approved

J Crichton *J.C.*
 Designation : Assistant Laboratory Manager
 Date : 12/06/18

PF-LAB-099 (20/03/2018)

Page 1 of 1

WSP Opus
 Napier Laboratory
 Quality Management Systems Certified to ISO 9001

90 Prebensen Drive
 Private Bag 6019, Hawkes Bay Mail
 Centre, Napier 4142, New Zealand

Telephone +64 6 833 5590
 Website www.wsp-opus.co.nz

**PLASTICITY INDEX FOR AGGREGATES
TEST REPORT**



Project : NCC Aquatic Centre
 Location : Napier
 Client : J. Yule, PO Box 5271, Auckland
 Contractor : Geotech Drilling
 Sampled by : Geotech Drilling
 Date sampled : 23/05/18
 Sampling method : Unknown
 Sample description : Sandy SILT
 Sample condition : Tested as received
 Source : BH 2 at 6.0m

Project No : 2-L0065.09
 Lab Ref No : NA 1717D
 Client Ref No : 1006598

Test Results	
Client Ref No :	1006598
Cone penetration limit :	29
Plastic limit :	NA
Plasticity index :	NP
Sample fraction :	That passing 425µm test sieve
Natural Water Content :	31.9%

Test Methods	Notes
Cone Penetration NZS 4407 : 2015 : Test 3.2	NA = Not attainable
Plastic Limit NZS 4407 : 2015 : Test 3.3	NP= Non plastic
Plasticity Index NZS 4407 : 2015 : Test 3.4	

Date tested : 11/06/18
 Date reported : 12/06/18

This report may only be reproduced in full

Approved

J Crichton

Designation : Assistant Laboratory Manager
 Date : 12/06/18

PF-LAB-053 (20/03/2018)

Page 1 of 1

WSP Opus
 Napier Laboratory
 Quality Management Systems Certified to ISO 9001

90 Prebensen Drive
 Private Bag 6019, Hawkes Bay Mail Centre,
 Napier 4142, New Zealand

Telephone +64 6 833 5590
 Website www.wsp-opus.co.nz


WET SIEVE ANALYSIS TEST REPORT



Project : NCC Aquatic Centre
 Location : Napier
 Client : J. Yule, PO Box 5271, Auckland
 Contractor : Geotech Drilling
 Sampled by : Geotech Drilling
 Date sampled : 23/05/18
 Sampling method : Unknown
 Sample description : Silty SAND
 Sample condition : Tested as received
 Bore hole no : 3
 Depth (m) : 6

Project No : 2-L0065.09
 Lab Ref No : NA 1717 E
 Client Ref No : 1006598

Sieve Analysis							
Size (mm)	% Passing	Size (mm)	% Passing	Size (mm)	% Passing	Size (mm)	% Passing
63.00	100	19.00	100	2.36	100	0.300	92
53.00	100	13.20	100	1.18	100	0.150	39
37.50	100	6.70	100	0.60	100	0.075	32
26.50	100	4.75	100	0.425	99	0.063	30



Test Method	Notes
NZS 4407 : 2015 Test 3.8.1	History: Ex BH 3 at 6.0m Fraction tested: Whole Dispersant Used: Nil <i>Fraction passing finest sieve is by difference.</i>

Date tested : 07/06/18
 Date reported : 12/06/18

This report may only be reproduced in full

Approved

J Crichton
 Designation : Assistant Laboratory Manager
 Date : 12/06/18

PF-LAB-099 (20/03/2018)

Page 1 of 1

WSP Opus
 Napier Laboratory
 Quality Management Systems Certified to ISO 9001


90 Prebensen Drive
 Private Bag 6019, Hawkes Bay Mail
 Centre, Napier 4142, New Zealand

Telephone +64 6 833 5590
 Website www.wsp-opus.co.nz

		Ground Floor, 19 Morgan Street, Newmarket, Auckland 1023 PO Box 9360, Newmarket, Auckland 1149 p 64 9 356 3510 www.geotechnics.co.nz	
Site: Aquatic Centre, Napier BH No.: 3 Test Method Used: NZS 4402:1986 Test 7.1 One-Dimensional Consolidation		Your Job No.: 1006598.0000 Our Job No.: 1007378.00000.0.0 Depth: 3.30-3.35 (m)	
ONE-DIMENSIONAL CONSOLIDATION TEST			
Pressure (kPa)	Void Ratio (e)	Pressure Increment (kPa)	Coefficient of Consolidation Cv (m ² /yr)
As received 0	1.689		
Preload 7.5	1.677	0 to 7.5	NA
15.1	1.666	7.5 to 15.1	9.0
30.2	1.637	15.1 to 30.2	7.8
60.3	1.584	30.2 to 60.3	6.3
121	1.463	60.3 to 121	5.4
241	1.293	121 to 241	4.6
483	1.118	241 to 483	4.3
Unload 15.1	1.281	483 to 15.1	NA
Sample History: Undisturbed core trimmed at NWC. Description: SILT with minor clay and trace of sand, soft, grey to dark grey. Initial Dry Density (t/m ³): 0.99 Initial Water Content: 61.5% Solid Density (t/m ³): 2.65 (Assumed) Initial Saturation: 96% Temperature During Testing: Max = 18 °C Min = 16 °C Remarks: SQR of time fitting method was used. We have assumed a standard value of 2.65 t/m ³ . The calculations of void ratio are affected by the solid density value. The test results are IANZ accredited but the sample description is not IANZ accredited.			
Entered by:	Date:	Checked by:	Date:


Appendix D : Liquefaction Assessment Outputs

- SLS Liquefaction Assessment
- 100 Year Recurrence Interval Liquefaction Assessment
- ULS Liquefaction Assessment




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fr (kN/m²)	γ (kN/m³)
INPUT	CPT01	112067	23/05/2018	User Specified			6.2	0.08	1.5 BI-2014	ZRB-2002				18
(Assumed pre-drill values)														
OUTPUT	PL	15%	3	0	0	0	0	0	0	0	0	0	0	0
		50%	0	0	0	0	0	0	0	0	0	0	0	0
		85%	0	0	0	0	0	0	0	0	0	0	0	0

	Tonkin + Taylor		CLIENT PROJECT		DATE	
	Exceptional thinking together		Napier City Council		12/06/2018	
	V1.3		Napier Aquatic Centre		joma	
			Liquefaction Analyses - SLS		ANALYSED	
					CHECKED	
					PAGE	
1006598						
		1 of 11 pages				




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
		TITLE		Liquefaction Analyses - SLS		JOB NUMBER 1006598	ANALYSED jona
							CHECKED PAGE
							2 of 11 pages








(Assumed pre-drill values)

CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	Magnitude	PGA & GWD	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT	CPT02	112104	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002					18
OUTPUT		PL	15%	4	0	0	0	0	0	0	0	0	0
			50%	0	0	0	0	0	0	0	0	0	0
			85%	0	0	0	0	0	0	0	0	0	0


	Tonkin + Taylor	CLIENT PROJECT				LOCATION	DATE
	Exceptional thinking together	Napier City Council				Napier	ANALYSED
	V1.3	Napier Aquatic Centre				JOB NUMBER	jona
		TITLE				1006598	CHECKED
		Liquefaction Analyses - SLS					PAGE
							3 of 11 pages




	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT		LOCATION	DATE	12/06/2018	
	Napier City Council Napier Aquatic Centre				Napier	ANALYSED	joma	
					JOB NUMBER	CHECKED		
			TITLE		1006598			
		Liquefaction Analyses - SLS					PAGE	4 of 11 pages




CPT Name	TTGD ID	Investigation Date	Event and Model	(PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
CPT03	112111	23/05/2018	User Specified			6.2	0.08	1.5 BI-2014	ZRB-2002		0	2	0.01
PL	SvdId (mm)	CTL (m)	LPI	LSN	CT (m)	LPlish							
OUTPUT	15%	8	0	0	1	10	0						
	50%	2	0	0	0	0	0						
	85%	0	0	0	0	10	0						

 Tonkin + Taylor Exceptional thinking together	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		DATE	12/06/2018
	TITLE		LOCATION		ANALYSED	joma
			Napier		CHECKED	
	V1.3		JOB NUMBER		PAGE	5 of 11 pages
				1006598		




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	Napier	DATE	12/06/2018
		TITLE		Liquefaction Analyses - SLS		JOB NUMBER	1006598	ANALYSED	jona
								CHECKED	




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT	CPT04	112112	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002				18
OUTPUT	PL											
	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh						
	15%	2	0	0	0	0						
	50%	0	0	0	0	10						
	85%	0	0	0	0	10						

	Tonkin + Taylor	CLIENT PROJECT	LOCATION		DATE	12/06/2018
	Exceptional thinking together	Napier City Council Napier Aquatic Centre	Napier		ANALYSED	joma
			JOB NUMBER		CHECKED	
			TITLE		1006598	
V1.3		Liquefaction Analyses - SLS				





	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT				DATE	12/06/2018
		Napier City Council Napier Aquatic Centre				LOCATION	Napier
						JOB NUMBER	1006598
		TITLE				ANALYSED	jona
		Liquefaction Analyses - SLS				CHECKED	
						PAGE	8 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	(Assumed pre-drill values)		
									qc (MPa)	Fs (MPa)	γ (kN/m³)
CPT01	112067	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
CPT02	112104	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
CPT03	112111	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
CPT04	112112	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0.02	2	0.01	18

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the left and right of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE	12/06/2018
		Napier City Council Napier Aquatic Centre		Napier	ANALYSED	joma
		TITLE		JOB NUMBER	CHECKED	
		Liquefaction Analyses - SLS		1006598	PAGE	9 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m²)
CPT01	112067	23/05/2018	User Specified	6.2	0.08	1.5	Bi-2014	ZRB-2002	0	0	2	0.01	18
CPT02	112104	23/05/2018	User Specified	6.2	0.08	1.5	Bi-2014	ZRB-2002	0	0	2	0.01	18
CPT03	112111	23/05/2018	User Specified	6.2	0.08	1.5	Bi-2014	ZRB-2002	0	0	2	0.01	18
CPT04	112112	23/05/2018	User Specified	6.2	0.08	1.5	Bi-2014	ZRB-2002	0.02	0	2	0.01	18

(Assumed pre-drill values)

Thicker lines represent the 50% probability of exceedence case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedence cases respectively.


	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE
		Napier City Council Napier Aquatic Centre		Napier	ANALYSED joma
				JOB NUMBER	CHECKED
				TITLE	
		Liquefaction Analyses - SLS		PAGE	

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112067	112104	112111	112112
CPT Name	CPT01	CPT02	CPT03	CPT04
PGA	0.08g	0.08g	0.08g	0.08g
Magnitude	6.2	6.2	6.2	6.2
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0.02m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	25m	25m	13.68m	23.08m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a


	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION	DATE
	TITLE		Liquefaction Analyses - SLS		ANALYSED Napier JOB NUMBER 1006598	12/06/2018 ANALYSED joma CHECKED PAGE 11 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	γ (kN/m ³)
INPUT	CPT06	112113	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
OUTPUT		PL	Svld (mm)	CTL (m)	LPI	LSN	CT (m)	LPish				
		15%	4	0	0	0	1	0				
		50%	0	0	0	0	0	0				
		85%	0	0	0	0	0	0				

(Assumed pre-drill values)

	Tonkin + Taylor		CLIENT PROJECT		DATE	
	Exceptional thinking together		Napier City Council		12/06/2018	
	V1.3		Napier Aquatic Centre		ANALYSED	
					jona	
					CHECKED	
					PAGE	
		TITLE		JOB NUMBER		
		Liquefaction Analyses - SLS		1006598		
				1 of 11 pages		




	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	DATE	12/06/2018	
	TITLE						Napier	ANALYSED	joma	
							JOB NUMBER		CHECKED	
							1006598		PAGE	2 of 11 pages
				Liquefaction Analyses - SLS						




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	q_c (MPa)	F_s (MPa)	γ (kN/m ³)
INPUT	CPT07	112114	24/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
OUTPUT		PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh				
		15%	2	0	0	0	0	0				
		50%	0	0	0	0	0	0				
		85%	0	0	0	0	0	0				

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	
	Exceptional thinking together		Napier City Council		Napier		ANALYSED joma	
	V1.3		Napier Aquatic Centre		JOB NUMBER		CHECKED	
			TITLE		1006598		PAGE	
			Liquefaction Analyses - SLS		3 of 11 pages			




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
	TITLE Liquefaction Analyses - SLS		JOB NUMBER 1006598	ANALYSED jona CHECKED PAGE 4 of 11 pages




(Assumed pre-drill values)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT	CPT08	112115	24/05/2018 User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh				
		15%	2	0	0	0	0				
		50%	0	0	0	0	0				
		85%	0	0	0	0	0				

	Tonkin + Taylor		Napier City Council		Napier Aquatic Centre		Napier		DATE		12/06/2018	
	Exceptional thinking together		V1.3		TITLE		JOB NUMBER		ANALYSED		joma	
			Liquefaction Analyses - SLS				1006598		CHECKED		PAGE	
											5 of 11 pages	




	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
			TITLE Liquefaction Analyses - SLS		JOB NUMBER 1006598	ANALYSED jona
						CHECKED PAGE 6 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g) & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	γ (kN/m³)
INPUT	CPT09	112116	24/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18		
	PL													
OUTPUT	15%	SV1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPlish							
	50%		3	0	0	1	10	0						
	85%		0	0	0	0	0	0						
			0	0	0	0	10	0						

	Tonkin + Taylor		CLIENT PROJECT		DATE		
	Exceptional thinking together		Napier City Council		12/06/2018		
	V1.3		Napier Aquatic Centre		ANALYSED joma		
					CHECKED		
			TITLE		PAGE		
		Liquefaction Analyses - SLS		1006598		7 of 11 pages	




<div>  </div> <div> Tonkin + Taylor Exceptional thinking together V1.3 </div>	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
	TITLE Liquefaction Analyses - SLS		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 8 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	(Assumed pre-drill values)		
									qc (MPa)	Fs (MPa)	γ (kN/m³)
CPT06	112113	23/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
CPT07	112114	24/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
CPT08	112115	24/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18
CPT09	112116	24/05/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the left and right of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE	12/06/2018
		Napier City Council Napier Aquatic Centre				
		Liquefaction Analyses - SLS				
		TITLE		JOB NUMBER	ANALYSED	jona
					CHECKED	
				PAGE	9 of 11 pages	




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE
		Napier City Council Napier Aquatic Centre		Napier	ANALYSED
				JOB NUMBER	CHECKED
				TITLE	
		Liquefaction Analyses - SLS		10 of 11 pages	

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112113	112114	112115	112116
CPT Name	CPT06	CPT07	CPT08	CPT09
PGA	0.08g	0.08g	0.08g	0.08g
Magnitude	6.2	6.2	6.2	6.2
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	22.64m	13.6m	10.9m	21.26m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a


	Tonkin + Taylor Exceptional thinking together		CLIENT, PROJECT		LOCATION		DATE	12/06/2018
	V1.3		Napier City Council Napier Aquatic Centre		Napier		ANALYSED	joma
					JOB NUMBER		CHECKED	
					TITLE		1006598	PAGE
			Liquefaction Analyses - SLS					




(Assumed pre-drill values)

INPUT	CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	γ (kN/m ³)
CPT05	112335	6/06/2018	User Specified	6.2	0.08	1.5	BI-2014	ZRB-2002						18
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh							
	15%	5	0	0	0	1	10	0						
	50%	1	0	0	0	0	10	0						
	85%	0	0	0	0	0	10	0						

	Tonkin + Taylor		CLIENT PROJECT		Napier City Council		LOCATION		DATE	
	Exceptional thinking together				Napier Aquatic Centre		Napier		ANALYSED	
	V1.3		TITLE				JOB NUMBER		CHECKED	
			Liquefaction Analyses - SLS				1006598		PAGE	
									1 of 5 pages	



 Tonkin + Taylor Exceptional thinking together	CLIENT / PROJECT		DATE	12/06/2018
	Napier City Council Napier Aquatic Centre		LOCATION	ANALYSED joma
	TITLE		JOB NUMBER	CHECKED
V1.3	Liquefaction Analyses - SLS		1005598	PAGE 2 of 5 pages




CPT Name	TTGD ID	Investigation Date	Event and Model (PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
CPT05	112335	6/06/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002		0	2	0.01	18

(Assumed pre-drill values)

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the left and right of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.

	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT		LOCATION		DATE	12/06/2018
	V1.3		Napier City Council Napier Aquatic Centre		Napier		ANALYSED	jona
					JOB NUMBER		CHECKED	
			TITLE		1006598		PAGE	3 of 5 pages
		Liquefaction Analyses - SLS						



(Assumed pre-drill values)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
CPT05	112335	6/06/2018	User Specified	6.2	0.08	1.5 BI-2014	ZRB-2002	0	2	0.01	18


Thicker lines represent the 50% probability of exceedance case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.

	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
			TITLE Liquefaction Analyses - SLS		JOB NUMBER 1006598	ANALYSED joma
					CHECKED PAGE	4 of 5 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.


Table 1.1-1 Summary of inputs for liquefaction analysis	
TTGD ID	112335
CPT Name	CPT05
PGA	0.08g
Magnitude	6.2
Depth to groundwater	1.5m
Predrill depth	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idress (2014)
Settlement method	Zhang, Robertson & Brachman (2002)
CFC	0
Total depth of CPT	14.84m
Maximum depth of analysis	10m
RL	n/a

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT			
		Napier City Council Napier Aquatic Centre			
		Liquefaction Analyses - SLS			
		TITLE			
		LOCATION			
		Napier			
		JOB NUMBER			
		1006598			
		DATE			
		12/06/2018			
ANALYSED					
joma					
CHECKED					
PAGE					
5 of 5 pages					




CPT Name		TTGD ID		Investigation Date		Event and Model (PGA & GWD)		Magnitude		PGA (g)		GWD (m)		Trigger Method		Settlement Method		Pre-drill Depth (m)		qc (MPa)		Fs (MPa)		γ (kN/m³)	
INPUT		CPT01		112067		23/05/2018		User Specified		6.2		0.17		1.5 BI-2014		ZRB-2002		0		0		2		0.01	
OUTPUT		PL		66		2.4		3		13		3.3		1		LPish		0		0		3.4		0	
		SV1d (mm)		37		1.4		1		7		3.4		0											
		CTL (m)		13		0		0		2		10		0											

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	
	Exceptional thinking together		Napier City Council		Napier		12/06/2018	
	V1.3		Napier Aquatic Centre		JOB NUMBER		ANALYSED joma	
							CHECKED	
							PAGE	
Liquefaction Analyses - 100yr				1006598		1 of 11 pages		




 Tonkin + Taylor Exceptional thinking together	CLIENT / PROJECT		Napier City Council Napier Aquatic Centre		DATE	12/06/2018
	TITLE		LOCATION		ANALYSED	joma
			JOB NUMBER		CHECKED	
V1.3		1 Immunofluorescence Analyses - 10hour		PAGE		2 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Magnitude	PGA (g)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT	CPT02	112104	23/05/2018	User Specified	6.2	0.17	1.5	BL-2014	ZRB-2002		0	2	0.01	18
OUTPUT	PL													
	Sv1d (mm)	73	2.9	3	13	2.6								
		15%	1.5	1	7	3.9								
		50%	0	0	3	10								
		85%												

	Tonkin + Taylor		CLIENT PROJECT		DATE		
	Exceptional thinking together		Napier City Council		12/06/2018		
	V1.3		Napier Aquatic Centre		jona		
						TITLE	
			Liquefaction Analyses - 100yr				
						LOCATION	
			Napier				
			JOB NUMBER				
			1006598			CHECKED	
						PAGE	
						3 of 11 pages	




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT / PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
		TITLE Liquefaction Analyses - 100yr		JOB NUMBER	ANALYSED joma
				1006598	CHECKED PAGE
		4 of 11 pages			




CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	γ (kN/m ³)
INPUT	CPT03	112111	23/05/2018	User Specified		6.2	0.17	1.5 Bi-2014	ZRB-2002				
OUTPUT	PL	15%	SvdId (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh					
		50%	114	3.7	6	21	2.5						
		85%	30	3.1	2	15	3.8						
			30	0.4	0	5	8						

	Tonkin + Taylor Exceptional thinking together	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		DATE	12/06/2018
		TITLE			LOCATION	ANALYSED joma	
					JOB NUMBER 1006598	CHECKED PAGE	5 of 11 pages




	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
					JOB NUMBER	ANALYSED jona
	TITLE Liquefaction Analyses - 100yr				1006598	CHECKED PAGE 6 of 11 pages




(Assumed pre-drill values)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	γ (kN/m ³)
INPUT	CPT04	112112	23/05/2018 User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0.02	2	0.01	18
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIish				
		15%	47	1.8	2	10	2.6				1
		50%	24	0.9	0	5	3.8				0
		85%	9	0	0	2	10				0

	Tonkin + Taylor		Napier City Council				DATE	12/06/2018	
	Exceptional thinking together		Napier Aquatic Centre				ANALYSED	jona	
	V1.3		Liquefaction Analyses - 100yr				LOCATION		Napier
							JOB NUMBER		1006598
							TITLE		
						CHECKED			
						PAGE	7 of 11 pages		




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT, PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
		TITLE Liquefaction Analyses - 100yr		JOB NUMBER	ANALYSED jona
					CHECKED PAGE
				1006598	8 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	Magnitude	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	(Assumed pre-drill values)		
										qc (MPa)	Fs (MPa)	γ (kN/m ³)
CPT01	112067	23/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	ZRB-2002	0	2	0.01	18
CPT02	112104	23/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	ZRB-2002	0	2	0.01	18
CPT03	112111	23/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	ZRB-2002	0	2	0.01	18
CPT04	112112	23/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	ZRB-2002	0.02	2	0.01	18

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the left and right of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	Napier	DATE	12/06/2018	
		TITLE		Liquefaction Analyses - 100yr		JOB NUMBER		1006598	ANALYSED	jona
								CHECKED		
								PAGE		9 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	γ (kN/m³)	
CPT01	112067	23/05/2018	User Specified		6.2	0.17	1.5 BI-2014	ZRB-2002		0	0	2	0.01	18
CPT02	112104	23/05/2018	User Specified		6.2	0.17	1.5 BI-2014	ZRB-2002		0	0	2	0.01	18
CPT03	112111	23/05/2018	User Specified		6.2	0.17	1.5 BI-2014	ZRB-2002		0	0	2	0.01	18
CPT04	112112	23/05/2018	User Specified		6.2	0.17	1.5 BI-2014	ZRB-2002		0.02	0.02	2	0.01	18

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.


	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT		LOCATION		DATE
	V1.3		Napier City Council Napier Aquatic Centre		Napier		12/06/2018
					JOB NUMBER		ANALYSED joma
					TITLE		CHECKED
			Liquefaction Analyses - 100yr		1006598		PAGE
						10 of 11 pages	

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis


TTGD ID	112067	112104	112111	112112
CPT Name	CPT01	CPT02	CPT03	CPT04
PGA	0.17g	0.17g	0.17g	0.17g
Magnitude	6.2	6.2	6.2	6.2
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0.02m
Assumed pre-drill tip resistance and skin friction	qc= 2MPa & fs= 0.01MPa	qc= 2MPa & fs= 0.01MPa	qc= 2MPa & fs= 0.01MPa	qc= 2MPa & fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	25m	25m	13.68m	23.06m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	DATE	12/06/2018
		TITLE		Liquefaction Analyses - 100yr		Napier	ANALYSED	jona
						JOB NUMBER	CHECKED	
								1006598




CPT Name		TTGD ID	Investigation Date	Event and Model	(PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
INPUT	CPT05	112335	6/06/2018	User Specified			6.2	0.17	1.5 BI-2014	ZRB-2002				18
OUTPUT	PL													
		15%	94	3.6	5	15								
		50%	57	2.3	1	9								
		85%	19	0	0	3								


CLIENT PROJECT		LOCATION		DATE	12/06/2018
	Tonkin + Taylor Exceptional thinking together V1.3	Napier City Council Napier Aquatic Centre		ANALYSED	joma
				CHECKED	
		Liquefaction Analyses - 100yr		PAGE	1 of 5 pages



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT				DATE	12/06/2018
		Napier City Council Napier Aquatic Centre				ANALYSED	joma
						TITLE	
						CHECKED	
						PAGE	2 of 5 pages



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	Napier	DATE	12/06/2018
		TITLE		Liquefaction Analyses - 100yr		JOB NUMBER	1006598	ANALYSED	jona
								CHECKED	



Vertical dotted lines indicate user specified PGA at the CPT locations. (actual PGA)

(Assumed pre-drill values)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
CPT05	112335	6/06/2018	User Specified	6.2	0.17	1.5	Bi-2014	ZRB-2002		0	2	0.01	18


Thicker lines represent the 50% probability of exceedence case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedence cases respectively.


	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE
		Napier City Council Napier Aquatic Centre		Napier	12/06/2018
		Liquefaction Analyses - 100yr		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 4 of 5 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112335
CPT Name	CPT05
PGA	0.17g
Magnitude	6.2
Depth to groundwater	1.5m
Predrill depth	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)
CFC	0
Total depth of CPT	14.84m
Maximum depth of analysis	10m
RL	n/a

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre TITLE Liquefaction Analyses - 100yr	LOCATION	DATE	12/08/2018
			Napier JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 5 of 5 pages	



CPT Name		TTGD ID	Investigation Date	Event and Model	(PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	γ (kN/m ³)
INPUT	CPT06	112113	23/05/2018	User Specified			6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIish							
		15%	67	2.5	3	13	1.9	2						
		50%	41	1.7	1	7	4.1	0						
		85%	14	0	0	3	10	0						
(Assumed pre-drill values)														
CPT Name														
INPUT														
OUTPUT														

Tonkin + Taylor
Exceptional thinking
together

CLIENT PROJECT
Napier City Council
Napier Aquatic Centre

TITLE
Liquefaction Analyses - 100yr

LOCATION
Napier


DATE
12/06/2018

ANALYSED
jona


CHECKED
PAGE

1006598

1 of 11 pages





 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
	TITLE Liquefaction Analyses - 100yr		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 2 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
INPUT	CPT07	112114	24/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0	0.01	2	18
OUTPUT	PL		CTL (m)	LPI	LSN	CT (m)	LPIsh					
			54	2.1	2	11	2					
			30	1.1	0	6	5.1					
			11	0	0	2	10					


	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	
	Exceptional thinking together		Napier City Council		Napier		ANALYSED joma	
	V1.3		Napier Aquatic Centre		JOB NUMBER		CHECKED	
			TITLE		1006598		PAGE	
			Liquefaction Analyses - 100yr		3 of 11 pages			




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
	TITLE Liquefaction Analyses - 100yr		JOB NUMBER 1006598	ANALYSED jona CHECKED PAGE 4 of 11 pages





CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	γ (kN/m ³)
INPUT	CPT08	112115	24/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18
(Assumed pre-drill values)												
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CTL (m)	LPlish					
	15%	45	1.8		2	7	5.1					
	50%	27	1		0	4	5.1					
	85%	9	0		0	1	10					




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
		TITLE Liquefaction Analyses - 100yr		JOB NUMBER 1006598	ANALYSED joma
				CHECKED	PAGE 6 of 11 pages




		Tonkin + Taylor		CLIENT, PROJECT		Napier City Council		LOCATION		DATE			
		Exceptional thinking together V1.3		TITLE		Napier Aquatic Centre		JOB NUMBER		ANALYSED jona			
Liquefaction Analyses - 100yr		1006598		PAGE		7 of 11 pages							
(Assumed pre-drill values)													
CPT Name		TTGD ID	Investigation Date	Event and Model (PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	γ (kN/m³)
CPT09		112116	24/05/2018	User Specified		6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18
INPUT													
OUTPUT		PL	SV/d (mm)	CTL (m)	LPI	LSN	CT (m)	LPlish					
		15%	56	2.1	3	9	4	0					
		50%	36	1.3	1	6	4	0					
		85%	12	0	0	2	10	0					



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT / PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	Napier	DATE	12/06/2018
		TITLE		Liquefaction Analyses - 100yr		JOB NUMBER	1006598		
								ANALYSED	joma
								CHECKED	
								PAGE	8 of 11 pages



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION		DATE	12/06/2018
		Napier City Council Napier Aquatic Centre		Napier		ANALYSED	jona
				JOB NUMBER		CHECKED	
		TITLE		Liquefaction Analyses - 100yr		1006598	



Vertical dashed lines indicate user specified PGA at the CPT locations. (Actual PGA)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	Assumed pre-drill values		
											qc (MPa)	Fs (MPa)	γ (kN/m³)
CPT06	112113	23/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18		
CPT07	112114	24/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18		
CPT08	112115	24/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18		
CPT09	112116	24/05/2018	User Specified	6.2	0.17	1.5 BI-2014	ZRB-2002	0	2	0.01	18		

Thicker lines represent the 50% probability of exceedence case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedence cases respectively.



Tonkin + Taylor

Exceptional thinking together

V1.3

CLIENT PROJECT

Napier City Council
Napier Aquatic Centre

LOCATION

Napier

DATE

12/06/2018

ANALYSED

joma

CHECKED

PAGE

10 of 11 pages

TITLE

Liquefaction Analyses - 100yr

JOB NUMBER


1006598

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis


TTGD ID	112113	112114	112115	112116
CPT Name	CPT06	CPT07	CPT08	CPT09
PGA	0.17g	0.17g	0.17g	0.17g
Magnitude	6.2	6.2	6.2	6.2
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	22.64m	13.6m	10.3m	21.26m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre TITLE Liquefaction Analyses - 100yr	LOCATION		DATE
			Napier	ANALYSED	12/06/2018
			JOB NUMBER	CHECKED	jona
			1006598	PAGE	11 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
INPUT	CPT01	112067	23/05/2018	User Specified			6.9	0.33	1.5 BI-2014	ZRB-2002				18
OUTPUT	PL	SV/d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIslush							
		15%	101	4	15	25	1.7	12						
		50%	96	3.8	11	23	1.9	8						
		85%	90	3.3	8	20	2.2	6						

	Tonkin + Taylor		CLIENT PROJECT		Napier City Council		LOCATION		DATE	
	Exceptional thinking together		Napier Aquatic Centre		Napier		ANALYSED		12/06/2018	
	V1.3		Liquefaction Analyses - ULS		JOB NUMBER		1006598		CHECKED	
							PAGE		1 of 11 pages	




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	DATE
	TITLE		Liquefaction Analyses - ULS		Napier JOB NUMBER	12/06/2018
					CHECKED PAGE	2 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	(PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
INPUT	CPT02	112104	23/05/2018	User Specified			6.9	0.33	1.5 Bi-2014	ZRB-2002				18
OUTPUT	PL	SVld (mm)	CTL (m)	LPI	LSN	CT (m)	LPlish							
	15%	107	4.2	15	24	1.6	12							
	50%	103	4	12	22	1.7	9							
	85%	98	3.7	9	20	2	6							

	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT		LOCATION		DATE		
	V1.3		Napier City Council Napier Aquatic Centre		Napier		ANALYSED		
					JOB NUMBER		CHECKED		
					1006598		PAGE		
		TITLE		Liquefaction Analyses - ULS					
				3 of 11 pages					




	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	DATE
		TITLE		Liquefaction Analyses - ULS		Napier	12/06/2018
						JOB NUMBER 1006598	ANALYSED jona CHECKED PAGE 4 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	(PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	γ (kN/m ³)
INPUT		CPT03	112111	23/05/2018	User Specified	6.9	0.33	1.5	BI-2014	ZRB-2002	0	0	2	18
OUTPUT		PL	SV1d (mm)	CTL (m)	LPI	LSN	CT (m)	LP1ish						
		15%	137	4.9	19	28	1.8	13						
		50%	133	4.6	16	27	2.1	11						
		85%	128	4.3	12	25	2.3	8						


	Tonkin + Taylor		CLIENT PROJECT		DATE		
	Exceptional thinking together		Napier City Council		12/06/2018		
	V1.3		Napier Aquatic Centre		joma		
			TITLE		ANALYSED		
			Liquefaction Analyses - ULS		JOB NUMBER		
				1006598		CHECKED	
						PAGE	
						5 of 11 pages	




 Tonkin + Taylor Exceptional thinking together	CLIENT PROJECT		DATE	12/06/2018
	Napier City Council Napier Aquatic Centre		LOCATION Napier	ANALYSED joma
	TITLE Liquefaction Analysis - ULS		JOB NUMBER 1005598	CHECKED PAGE
V1.3		6 of 11 pages		




(Assumed pre-drill values)												
CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
CPT04		112112	23/05/2018	User Specified	6.9	0.33	1.5 BI-2014	ZRB-2002	0.02	2	0.01	18
INPUT												
OUTPUT	PL	15%	Sv1d (mm)	69	2.7	LPI	10	17	1.6	LPlish		
		50%		67	2.5		8	16	1.6	6		
		85%		63	2.5		6	15	1.6	4		


	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT	Napier City Council Napier Aquatic Centre		LOCATION	Napier	DATE	12/06/2018
	V1.3		TITLE	Liquefaction Analysis - ULS		JOB NUMBER	1006598	ANALYSED	joma
								CHECKED	
								PAGE	7 of 11 pages



 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE
	Napier City Council Napier Aquatic Centre		Napier	ANALYSED joma
			JOB NUMBER	CHECKED
TITLE		PAGE 8 of 11 pages		
		Liquefaction Analyses - ULS		



	Tonkin + Taylor		CLIENT PROJECT		Napier City Council		LOCATION	DATE	12/06/2018	
	Exceptional thinking together				Napier Aquatic Centre		Napier	ANALYSED	jona	
	V1.3						JOB NUMBER	CHECKED		
					Liquefaction Analyses - ULS		1006598			
				TITLE					PAGE	9 of 11 pages



Vertical dotted lines indicate user specified PGA at the CPT locations. (Actual PGA)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	(Assumed pre-drill values)	
											qc (MPa)	Fs (MPa)
CPT01	112067	23/05/2018	User Specified	6.9	0.33	1.5 BI-2014	ZRB-2002	0	2	0.01	18	18
CPT02	112104	23/05/2018	User Specified	6.9	0.33	1.5 BI-2014	ZRB-2002	0	2	0.01	18	18
CPT03	112111	23/05/2018	User Specified	6.9	0.33	1.5 BI-2014	ZRB-2002	0	2	0.01	18	18
CPT04	112112	23/05/2018	User Specified	6.9	0.33	1.5 BI-2014	ZRB-2002	0.02	2	0.01	18	18

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.



Tonkin + Taylor

Exceptional thinking together

V1.3

CLIENT PROJECT

Napier City Council
Napier Aquatic Centre

TITLE

Liquefaction Analyses - ULS

LOCATION

Napier

JOB NUMBER

1006598

DATE

12/06/2018

ANALYSED

joma

CHECKED

PAGE


10 of 11 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112067	112104	112111	112112
CPT Name	CPT01	CPT02	CPT03	CPT04
PGA	0.33g	0.33g	0.33g	0.33g
Magnitude	6.9	6.9	6.9	6.9
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0.02m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	25m	25m	13.68m	23.08m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a

	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT		LOCATION		DATE
			Napier City Council Napier Aquatic Centre		Napier		ANALYSED joma
					JOB NUMBER 1006598		CHECKED
	TITLE		Liquefaction Analyses - ULS				PAGE 11 of 11 pages



CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	γ (kN/m ³)
INPUT	CPT05	112335	6/06/2018	User Specified	6.9	0.33	1.5 BI-2014	ZRB-2002				18
OUTPUT	PL											
		Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LP1ish					
		15%	106	3.9	16	17	3.8	10				
		50%	106	3.9	13	17	3.8	8				
		85%	106	3.9	11	17	3.8	7				

Tonkin + Taylor
Exceptional thinking
together
V1.3

CLIENT PROJECT

Napier City Council
Napier Aquatic Centre

TITLE

Liquefaction Analyses - ULS

LOCATION

Napier

JOB NUMBER

1006598

DATE

12/06/2018


ANALYSED


joma


CHECKED

PAGE


1 of 5 pages



 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 12/06/2018
	TITLE Liquefaction Analyses - ULS		JOB NUMBER 1006598	ANALYSED jona CHECKED PAGE 2 of 5 pages



	Tonkin + Taylor		CLIENT PROJECT	Napier City Council		LOCATION	Napier		DATE		12/06/2018				
	Exceptional thinking together			Napier Aquatic Centre			ANALYSED		joma						
	V1.3			Liquefaction Analyses - ULS			JOB NUMBER		1006598		CHECKED		PAGE		3 of 5 pages
						TITLE									




<div>  <div> <div>Tonkin + Taylor</div> <div>Exceptional thinking together</div> <div>V1.3</div> </div> </div>	CLIENT / PROJECT		LOCATION		DATE	12/06/2018
	Napier City Council Napier Aquatic Centre		Napier		ANALYSED	joma
	Liquefaction Analyses - ULS		JOB NUMBER 1006598		CHECKED	PAGE 4 of 5 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis


TTGD ID	112335
CPT Name	CPT05
PGA	0.33g
Magitude	6.9
Depth to groundwater	1.5m
Predrill depth	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)
CFC	0
Total depth of CPT	14.84m
Maximum depth of analysis	10m
RL	n/a

 <div> <div>Tonkin + Taylor</div> <div>Exceptional thinking together</div> <div>V1.3</div> </div>	CLIENT PROJECT		DATE	
	Napier City Council		12/06/2018	
	Napier Aquatic Centre		joma	
TITLE	LOCATION		ANALYSED	
	Napier		CHECKED	
Liquefaction Analyses - ULS		JOB NUMBER		PAGE
		1006598		5 of 5 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
CPT06		112113	23/05/2018	User Specified	6.9	0.33	1.5	BI-2014	ZRB-2002					18
OUTPUT	PL	Svrd (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh							
	15%	87	3.2	12	20	20	10							
	50%	85	3.1	10	20	20	8							
	85%	83	3	8	19	19	6							

	Tonkin + Taylor	CLIENT PROJECT	Napier City Council		LOCATION	DATE	
	Exceptional thinking together		Napier Aquatic Centre		Napier	ANALYSED joma	
	V1.3				JOB NUMBER	CHECKED	
			TITLE	1006598			
			Liquefaction Analyses - ULS	PAGE 1 of 11 pages			




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		DATE	12/06/2018
	Napier City Council Napier Aquatic Centre		ANALYSED	joma
	TITLE		LOCATION	Napier
			JOB NUMBER	
			1006598	
Liquefaction Analyses - ULS		PAGE	2 of 11 pages	




		(Assumed pre-drill values)									
		PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)			
INPUT		112114	0.33	1.5 BI-2014	ZRB-2002	0	2	0.01			
OUTPUT		PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIish			
		15%	76	2.7	11	20	1.6	10			
		50%	76	2.7	9	20	1.6	8			
		85%	75	2.7	7	20	1.6	5			

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	12/06/2018
	Exceptional thinking together		Napier City Council Napier Aquatic Centre		Napier		ANALYSED	joma
	V1.3		TITLE Liquefaction Analyses - ULS		JOB NUMBER		CHECKED	
PAGE							1006598 3 of 11 pages	




	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT		LOCATION		DATE	12/06/2018
	V1.3		Napier City Council Napier Aquatic Centre		Napier		ANALYSED	joma
					JOB NUMBER		CHECKED	
					TITLE		1006598	PAGE
			Liquefaction Analyses - ULS					




CPT Name		TTGD ID	Investigation Date	Event and Model (PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
CPT08		112115	24/05/2018	User Specified		6.9	0.33	1.5 BI-2014	ZRB-2002				18
OUTPUT	PL												
		58	2.3	9	9	5.1	5						
		57	2.3	6	9	5.1	3						


	Tonkin + Taylor		CLIENT PROJECT		DATE		
	Exceptional thinking together		Napier City Council		ANALYSED		
	V1.3		Napier Aquatic Centre		joma		
			TITLE			JOB NUMBER	
			Liquefaction Analyses - ULS			1006598	
			PAGE			5 of 11 pages	




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre	LOCATION	Napier	DATE	12/06/2018
	TITLE		Liquefaction Analyses - ULS	JOB NUMBER	1006598	ANALYSED	joma
						CHECKED	
						PAGE	6 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m²)
(Assumed pre-drill values)														
INPUT	CPT09	112116	24/05/2018	User Specified			6.9	0.33	1.5 BI-2014	ZRB-2002			2	0.01
OUTPUT	PL				LSN	CTL (m)	LPI	LPLish						18
	15%	69	2.6	10	12	1.7		6						
	50%	68	2.6	8	12	1.7		5						
	85%	66	2.5	6	12	1.7		4						


 Tonkin + Taylor Exceptional thinking together	CLIENT PROJECT		DATE		12/06/2018
	Napier City Council Napier Aquatic Centre		LOCATION	ANALYSED	joma
			TITLE I Ionofraction Analyses - III S	Napier JOB NUMBER 1006598	CHECKED PAGE 7 of 11 pages



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	Napier	DATE	12/06/2018
		TITLE		Liquefaction Analyses - ULS		JOB NUMBER	1006598	ANALYSED	jona
								CHECKED	



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE	12/06/2018		
		Napier City Council Napier Aquatic Centre		Napier	ANALYSED	jona		
				JOB NUMBER	CHECKED			
		TITLE		Liquefaction Analyses - ULS		1006598	PAGE	9 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	(Assumed pre-drill values)		
											qc (MPa)	Fs (MPa)	γ (kN/m³)
CPT06	112113	23/05/2018	User Specified		6.9	0.33	1.5 Bi-2014	ZRB-2002		0	2	0.01	18
CPT07	112114	24/05/2018	User Specified		6.9	0.33	1.5 Bi-2014	ZRB-2002		0	2	0.01	18
CPT08	112115	24/05/2018	User Specified		6.9	0.33	1.5 Bi-2014	ZRB-2002		0	2	0.01	18
CPT09	112116	24/05/2018	User Specified		6.9	0.33	1.5 Bi-2014	ZRB-2002		0	2	0.01	18

Thicker lines represent the 50% probability of exceedence case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedence cases respectively.



Tonkin + Taylor

Exceptional thinking together

V1.3

CLIENT PROJECT

Napier City Council
Napier Aquatic Centre

Liquefaction Analyses - ULS

LOCATION

Napier

DATE

12/06/2018

ANALYSED

joma

CHECKED

PAGE


10 of 11 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112113	112114	112115	112116
CPT Name	CPT06	CPT07	CPT08	CPT09
PGA	0.33g	0.33g	0.33g	0.33g
Magnitude	6.9	6.9	6.9	6.9
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	22.64m	13.6m	10.0m	21.26m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a

 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		DATE		12/06/2018		
	Napier City Council Napier Aquatic Centre		LOCATION		ANALYSED	joma	
			JOB NUMBER		CHECKED		
	TITLE		1006598		PAGE		11 of 11 pages
	Liquefaction Analyses - ULS						



(Assumed pre-drill values)

FS (MPa) q_c (MPa) γ (kN/m³)

0 2 0.01 18

Pre-drill Depth (m)

0 2 0.01 18

Trigger Method Settlement Method ZRB-2002

PGA (g) GWD (m) 1.5 BI-2014

0.43 0.43 1.5 BI-2014

LPish

16

13

10

Magnitude

6.9 0.43

0.43

1.5 BI-2014

LPish

16

13

10

CT (m)

27 16

16

13

24

24

24

24

LSN

18 27

16

13

24

24

24

24

LPI

4.2 105

103

98

105

103

98

105

CTL (mm)

105 103

98

105

103

98

105

103

SV1d (mm)

105 103

98

105

103

98

105

103

PL

15%

50%

85%

15%

50%

85%

OUTPUT

15%

50%


85%

15%


50%

85%

	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT		LOCATION		DATE	
	V1.3		Napier City Council Napier Aquatic Centre		Napier		ANALYSED joma	
			TITLE		JOB NUMBER		CHECKED	
			Liquefaction Analyses		1006598		PAGE	
							1 of 11 pages	





 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
	TITLE Liquefaction Analyses		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 2 of 11 pages




CPT Name		TTGD ID		Investigation Date		Event and Model (PGA & GWD)		Magnitude		PGA (g)		GWD (m)		Trigger Method		Settlement Method		Pre-drill Depth (m)		Fs (MPa)		Y (kN/m²)	
INPUT		CPT02		112104		23/05/2018		User Specified		6.9		0.43		1.5 BI-2014		ZRB-2002		0		2		0.01	
OUTPUT		PL		Sv1d (mm)		CTL (m)		LPI		LSN		CT (m)		LPIish									
				15%		109		4.3		19		25		1.6		15							
				50%		108		4.2		16		25		1.6		12							
				85%		104		4.1		13		23		1.7		10							

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	
	Exceptional thinking together		Napier City Council		Napier		13/06/2018	
	V1.3		Napier Aquatic Centre		JOB NUMBER		ANALYSED	
			Liquefaction Analyses		1006598		CHECKED	
			TITLE				PAGE	
					3 of 11 pages			




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
	TITLE Liquefaction Analyses		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 4 of 11 pages




CPT Name		TTGD ID	Investigation Date	Event and Model (PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT		CPT03	112111	23/05/2018	User Specified	6.9	0.43	1.5 Bi-2014	ZRB-2002				18
OUTPUT		PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh					
			15%	141	5.1	23	31	1.7					
			50%	138	4.9	20	29	1.8					
			85%	134	4.7	17	27	2.1					


	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	
	Exceptional thinking together		Napier City Council		Napier		13/06/2018	
	V1.3		Napier Aquatic Centre		JOB NUMBER		ANALYSED joma	
					1006598		CHECKED	
			Liquefaction Analyses				PAGE	
		TITLE				5 of 11 pages		




	Tonkin + Taylor Exceptional thinking together	Napier City Council Napier Aquatic Centre I Liquefaction Analyses	CLIENT PROJECT		DATE	13/06/2018
	V1.3		LOCATION		ANALYSED	joma
			JOB NUMBER		CHECKED	
			TITLE		1006598	PAGE




	CPT Name	TTGD ID	Investigation Date	Event and Model	PGA & GWD			Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	(Assumed pre-drill values)		
					User Specified	LSN	CT (m)							qc (MPa)	Fs (MPa)	γ (kN/m²)
INPUT	CPT04	112112	23/05/2018						6.9	0.43	1.5 BI-2014	ZRB-2002	0.02	2	0.01	18
OUTPUT	PL	SVd1d (mm)	CTL (m)	LPI		LSN	CT (m)									
		15%	71	2.8		13	17			1.6						
		50%	69	2.7	11		17			1.6	9					
		85%	68	2.6		9	17			1.6	7					


	Tonkin + Taylor Exceptional thinking together	CLIENT PROJECT		DATE	13/06/2018
		Napier City Council Napier Aquatic Centre		LOCATION	ANALYSED joma
		TITLE		Napier JOB NUMBER	CHECKED
		I Louefraction Analyses		1006598	PAGE
					7 of 11 pages



 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
	TITLE Liquefaction Analyses		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 8 of 11 pages



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION		DATE	13/06/2018
		Napier City Council Napier Aquatic Centre		Napier		ANALYSED	joma
		TITLE		JOB NUMBER		CHECKED	
		Liquefaction Analyses		1006598		PAGE	9 of 11 pages



CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	γ (kN/m³)
CPT01	112067	23/05/2018	User Specified	6.9	0.43	1.5 BI-2014	ZRB-2002	0	0	2	0.01
CPT02	112104	23/05/2018	User Specified	6.9	0.43	1.5 BI-2014	ZRB-2002	0	0	2	0.01
CPT03	112111	23/05/2018	User Specified	6.9	0.43	1.5 BI-2014	ZRB-2002	0	0	2	0.01
CPT04	112112	23/05/2018	User Specified	6.9	0.43	1.5 BI-2014	ZRB-2002	0.02	0.02	2	0.01

Thicker lines represent the 50% probability of exceedance case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedance cases respectively.


	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE
		Napier City Council Napier Aquatic Centre		Napier	ANALYSED
		TITLE		JOB NUMBER	CHECKED
		Liquefaction Analyses		1006598	PAGE
					10 of 11 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis


TTGD ID	112067	112104	112111	112112
CPT Name	CPT01	CPT02	CPT03	CPT04
PGA	0.43g	0.43g	0.43g	0.43g
Magnitude	6.9	6.9	6.9	6.9
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0.02m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	25m	25m	13.68m	23.06m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		Napier City Council Napier Aquatic Centre Liquefaction Analyses	LOCATION		DATE	13/06/2018
		TITLE			Napier	ANALYSED	jona	
					JOB NUMBER	CHECKED		
					1006598	PAGE	11 of 11 pages	




CPT Name		TTGD ID	Investigation Date	Event and Model (PGA & GWD)	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT		CPT05	112335	6/06/2018	User Specified	6.9	0.43	1.5 BI-2014	ZRB-2002	0	2	18
OUTPUT		PL	15%	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh			
			50%	106	3.9	18	17	3.8	11			
			85%	106	3.9	16	17	3.8	10			


	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	
	Exceptional thinking together		Napier City Council		Napier		ANALYSED joma	
	V1.3		Napier Aquatic Centre		JOB NUMBER		CHECKED	
			Liquefaction Analyses		1006598		PAGE 1 of 5 pages	



 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		DATE	
	Napier City Council Napier Aquatic Centre		13/06/2018	
	TITLE		LOCATION	
			Napier	
			JOB NUMBER	
			1006598	
			ANALYSED	
			joma	
		CHECKED		
		PAGE		
		2 of 5 pages		
Liquefaction Analyses				



	Tonkin + Taylor Exceptional thinking together V1.3		CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
	TITLE Liquefaction Analyses		JOB NUMBER 1006598		ANALYSED jona	CHECKED PAGE 3 of 5 pages



CPT Name TTGD ID Investigation Date Event and Model (PGA & GWD) Magnitude PGA (g) GWD (m) Trigger Method Settlement Method Pre-drill Depth (m) qc (MPa) Fs (MPa) γ (kN/m³)

■ CPT05 112335 6/06/2018 User Specified 6.9 0.43 1.5 BI-2014 ZRB-2002 0 0 0.01 18

Thicker lines represent the 50% probability of exceedence case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedence cases respectively.


	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT				LOCATION	DATE
		Napier City Council Napier Aquatic Centre Liquefaction Analyses				Napier	13/06/2018
						JOB NUMBER	ANALYSED joma
						1006598	4 of 5 pages

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112335
CPT Name	CPT105
PGA	0.43g
Magnitude	6.9
Depth to groundwater	1.5m
Predrill depth	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)
CFC	0
Total depth of CPT	14.84m
Maximum depth of analysis	10m
RL	n/a


	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT			
		Napier City Council Napier Aquatic Centre			
		TITLE			
		Liquefaction Analyses			
		LOCATION		Napier	
		JOB NUMBER		1006598	
		DATE		13/06/2018	
		ANALYSED		joma	
		CHECKED			
		PAGE			
		5 of 5 pages			




(Assumed pre-drill values)

CPT Name	TTGD ID	Investigation Date	Event and Model (PGA & GWD)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	FS (MPa)	Y (kN/m ²)
INPUT	CPT06	112113	23/05/2018 User Specified		6.9	0.43	1.5 BI-2014	ZRB-2002	0	2	0.01	18
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIish					
		15%	88	3.2	15	20	1.6	12				
		50%	87	3.2	13	20	1.6	10				
		85%	86	3.1	11	20	1.6	8				

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE							
	Exceptional thinking together		Napier City Council		Napier		13/06/2018							
	V1.3		Napier Aquatic Centre		JOB NUMBER		ANALYSED joma							
						TITLE			1006598			CHECKED		
						Liquefaction Analyses						PAGE		
									1 of 11 pages					




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
	TITLE Liquefaction Analyses		JOB NUMBER 1006598	ANALYSED joma CHECKED PAGE 2 of 11 pages




CPT Name		TTGD ID		Investigation Date		Event and Model (PGA & GWD)		Magnitude		PGA (g)		GWD (m)		Trigger Method		Settlement Method		Pre-drill Depth (m)		qc (MPa)		Fs (MPa)		γ (kN/m³)	
CPT07		112114		24/05/2018		User Specified		6.9		0.43		1.5 BI-2014		ZRB-2002		0		2		0.01		18			
OUTPUT	PL	Sv1d (mm)		CTL (m)		LPI		LSN		CT (m)		LPlish													
	15%	77		2.8		13		20		1.6		11													
	50%	76		2.8		12		20		1.6		10													
		76		2.7		10		20		1.6		8													

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE		
	Exceptional thinking together		Napier City Council		Napier		13/06/2018		
	V1.3		Napier Aquatic Centre		JOB NUMBER		ANALYSED joma		
			TITLE		1006598		CHECKED		
			Liquefaction Analyses				PAGE		
								3 of 11 pages	




<div>  </div> <div> Tonkin + Taylor Exceptional thinking together V1.3 </div>	<div> CLIENT PROJECT Napier City Council Napier Aquatic Centre </div>		<div> LOCATION Napier </div>	<div> DATE 13/06/2018 </div>
	<div> TITLE Liquefaction Analyses </div>		<div> JOB NUMBER 1006598 </div>	<div> ANALYSED joma </div>
			<div> CHECKED PAGE </div>	<div> 4 of 11 pages </div>




CPT Name		TTGD ID	Investigation Date	Event and Model	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	Y (kN/m ²)
INPUT	CPT08	112115	24/05/2018	User Specified	6.9	0.43	1.5 BI-2014	ZRB-2002	0	2	0.01	18
OUTPUT		PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPIsh				
		15%	58	2.3	10	9	9	5.1	6			
		50%	58	2.3	9	9	9	5.1	5			
		85%	58	2.3	8	9	9	5.1	5			

	Tonkin + Taylor		CLIENT PROJECT		LOCATION		DATE	13/06/2018
	Exceptional thinking together		Napier City Council		Napier		ANALYSED	joma
	V1.3		Napier Aquatic Centre		JOB NUMBER		CHECKED	
			TITLE		1006598		PAGE	5 of 11 pages
		Liquefaction Analyses						




 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
	TITLE Liquefaction Analyses		JOB NUMBER 1006598	ANALYSED jona CHECKED PAGE 6 of 11 pages




(Assumed pre-drill values)

CPT Name		TTGD ID Investigation Date Event and Model (PGA & GWD)		PGA (g)		GWD (m)		Trigger Method		Settlement Method		Pre-drill Depth (m)		qc (MPa)		Fs (MPa)		Y (kN/m ²)	
INPUT	CPT09	112116	24/05/2018	User Specified	6.9	0.43	1.5	BI-2014	ZRB-2002			0	2	0.01	18				
OUTPUT	PL	Sv1d (mm)	CTL (m)	LPI	LSN	CT (m)	LPlish												
		15%	71	2.7	12	12	1.7												
		50%	70	2.6	10	12	1.7												
		85%	69	2.6	9	12	1.7												


	Tonkin + Taylor		Napier City Council		Napier Aquatic Centre		Liquefaction Analyses				
	Exceptional thinking together										
	V1.3										
CLIENT PROJECT		LOCATION		DATE		ANALYSED		CHECKED		PAGE	
		Napier		13/06/2018		joma				7 of 11 pages	
		JOB NUMBER									
		1006598									



	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT Napier City Council Napier Aquatic Centre		LOCATION Napier	DATE 13/06/2018
		TITLE Liquefaction Analyses		JOB NUMBER 1006598	ANALYSED joma
					CHECKED
				PAGE	8 of 11 pages



 Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		DATE	13/06/2018
	Napier City Council Napier Aquatic Centre	LOCATION	ANALYSED	joma
		TITLE	JOB NUMBER	CHECKED
	Liquefaction Analyses	1006598	PAGE	9 of 11 pages



Vertical dotted lines indicate user specified PGA at the CPT locations. (actual PGA)

CPT Name	TTGD ID	Investigation Date	Event and Model	PGA (g)	Magnitude	PGA (g)	GWD (m)	Trigger Method	Settlement Method	Pre-drill Depth (m)	qc (MPa)	Fs (MPa)	(Assumed pre-drill values)	
													Y (kN/m ²)	Y (kN/m ²)
CPT06	112113	23/05/2018	User Specified	6.9	0.43	6.9	1.5 Bi-2014	ZRB-2002	ZRB-2002	0	2	0.01	18	18
CPT07	112114	24/05/2018	User Specified	6.9	0.43	6.9	1.5 Bi-2014	ZRB-2002	ZRB-2002	0	2	0.01	18	18
CPT08	112115	24/05/2018	User Specified	6.9	0.43	6.9	1.5 Bi-2014	ZRB-2002	ZRB-2002	0	2	0.01	18	18
CPT09	112116	24/05/2018	User Specified	6.9	0.43	6.9	1.5 Bi-2014	ZRB-2002	ZRB-2002	0	2	0.01	18	18

Thicker lines represent the 50% probability of exceedence case and the thinner lines to the bottom and top of the thicker lines represent the 85% and 15% probability of exceedence cases respectively.

	Tonkin + Taylor Exceptional thinking together V1.3	CLIENT PROJECT		LOCATION	DATE	13/06/2018		
		Napier City Council Napier Aquatic Centre					Napier	ANALYSED
				TITLE	JOB NUMBER	CHECKED		
						1006598	PAGE	10 of 11 pages
				Liquefaction Analyses				

The inputs listed in Table 1.1-1 below have been adopted for the liquefaction analysis.

Table 1.1-1 Summary of inputs for liquefaction analysis

TTGD ID	112113	112114	112115	112116
CPT Name	CPT06	CPT07	CPT08	CPT09
PGA	0.43g	0.43g	0.43g	0.43g
Magnitude	6.9	6.9	6.9	6.9
Depth to groundwater	1.5m	1.5m	1.5m	1.5m
Predrill depth	0m	0m	0m	0m
Assumed predrill tip resistance and skin friction	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa	qc= 2MPa & Fs= 0.01MPa
Trigger method	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)	Boulanger & Idriss (2014)
Settlement method	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)	Zhang, Robertson & Brachman (2002)
CFC	0	0	0	0
Total depth of CPT	22.64m	13.6m	10.9m	21.26m
Maximum depth of analysis	10m	10m	10m	10m
RL	n/a	n/a	n/a	n/a

	Tonkin + Taylor Exceptional thinking together		CLIENT PROJECT		Napier City Council Napier Aquatic Centre		LOCATION	DATE	13/06/2018
	V1.3		TITLE				Napier	ANALYSED	joma
							JOB NUMBER	CHECKED	
							1006598	PAGE	11 of 11 pages


Appendix E : Historical Aerial Photographs













Ashburton EA Networks Centre: Case Study

The EA Networks Centre in Ashburton is an 8,000m² multi-discipline sports facility combining indoor courts, an aquatic centre and a gym. The facility was completed in 2015 at a cost of \$30 million.

The current gym is 521m² including small group fitness studio and spin room. Before construction the new (at the time) Sports Facilities Manager at Ashburton District Council expressed reservations around the size of the gym, but the construction budget at the time could not cater for any increases in footprint.

Upon opening, the gym had a goal of attracting 500-600 members in a town of 34,000 population. Membership reached 1,100 within the first year, meaning that the relatively small facility was at capacity almost straight away. This was within a town that was previously well catered for in terms of the number of commercial gyms.

Of the complaints that were received, by far the most common was the lack of space. This particularly affected group fitness classes that due to space constraints need to be capped to ensure safety and quality of experience, but meaning that many that wanted to participate were not able to be catered for.

A review of the fitness centre after three years of operation was completed, that revealed a net financial contribution of \$125,000 per annum. It also revealed significant synergy between the dry and wet components of the centre, with a large percent of membership paying a premium fee to be able to use both the aquatic and dry fitness facilities.

To respond to the needs of the community and increase capacity and therefore revenue potential, a plan has been developed to increase the dry-side space by an additional 200m² (bringing total area to 721m²) at a cost of approximately \$500,000. This estimate is calculated on the cost of \$2,500 per m². Due to additional plans to add to the number of indoor courts, the gym extension will be included in the same construction contract, with the work to be commenced in three years' time. The reason for this would be to get a cost saving due to it being part of a larger project